

GASOILA

Spray Lubricants / Anti-Seize & Lubricating Compound / Light Thread Cutting Oil

Lube-It All® Deep Lubricating Oil (LA01 1 oz)

- Contains Molybdenumdisulphide for superior lubricating performance!
- Silicone-free formula.
- Does not attract dust.
- Forms a thin, dry lubricant coating to reduce friction.
- Displaces 1,200 times its volume in water on surfaces and repels moisture to prevent corrosion.
- Penetrates through fine gaps to deliver coating to assembled parts and obstructed surfaces.
- Can be used on electrical, metal and plastic surfaces, rotating parts and gears.
- Temperature Range: -30°F to 350°F (-34°C to 177°C).



Lube-It All® 450 Food Grade Lubricant (LA450 12 oz)

- NSF H1 • Silicone free.
- Economical-general purpose lubricant.
- Penetrates and loosens dirt.
- Safe on styrenes and urethanes.
- Works on paint, metal, plastic & wood.
- Virtually odorless and tack less.
- Temperature Range: -20°F to 450°F (-29°C to 232°C)



Premium White Grease Long-Lasting White Lithium Grease (WG16 14 oz)

- High solid, non-staining white grease.
- Will not run or drip on vertical surfaces.
- Effective from -20°F to 275°F.
- Use on chains, gears, drives, hinges and other overhead surfaces.
- Forms a complete coating around moving parts.
- Protects metal surfaces against rust and wear.
- Safe on plastics and painted surfaces.



Lube-It All® 525 Food Grade Lubricant (LA525 12 oz)

- NSF H1 • 5% silicone.
- Colorless, odorless low viscosity formula.
- Safe on styrenes and urethanes.
- Stops sticking without transfer.
- Temperature Range: -40°F to 450°F (-40°C to 232°C).



Free All® Deep Penetrating Oil (RE01 1 oz)

- Penetrates rust, scale and corrosion to free parts and assemblies INSTANTLY!
- Loosens red and white lead, tar, grease, carbon and graphite deposits.
- Specially formulated, rust eating agent is ideal for plumbing, automotive, marine and general industrial applications.
- No more torching, drilling, hammering or chiseling.
- Will free up all threaded pipe connections, rusted machine screws, bolts, nuts, clamps for mufflers and tail pipes, pillow blocks, universal joints, locks, etc.
- Contains NO silicones, making it safe in paint and shop environments.



Thred Gard® Anti-Seize & Lubricating Compound

- Provides protection against seizing, galling, rust and corrosion.
- Brush on nuts, bolts, screws, bushings, cam rollers, shafts, sleeves, couplings, conveyers, motors, pumps, turbines, valves, etc.
- Speeds assembly, facilitates disassembly.
- Industry applications include steel mills, forges, foundries, die casters, refining and chemical installations, marine services, farm and construction equipment, power and utility plants, paper and pulp mills and general plant maintenance.
- Non-hardening, non-dripping.
- Exceeds MIL Spec MIL-A-907D.

Safe for temperatures up to:

General Purpose
(TG04 ¼ lb brush)

1,000°F/537°C.



Copper Based
(CG04 ¼ lb. brush)

1,800°F/982°C



Nickel Based
(NG04 ¼ lb. brush)

2,600°F/1,427°C



Light Thread Cutting Oil (WL32 1 qt, WL28 1 gal)

- Premium-grade cutting oil extends die life by cleaning threads, dissipating heat and reducing friction.
- Non-staining, transparent, low-odor oil that provides protection under heavy loads and high speeds.
- Contains NO chlorine or other halogens, PCB's or heavy metals.
- Listed as non-carcinogenic by the EPA and OSHA.

