


F-2983-M 2 1/2"-6"

Iron Globe Valve
250 SWP - 500 WOG †
Solid Wedge Disc
Bolted Bonnet • Flanged Ends
Conforms to: MSS SP-85

Flange shape and drilling to specification ASME B16.1 (250 lb.)



MATERIAL LIST

No.	PART	MATERIAL	SPECIFICATION
1	Handwheel Nut	Steel	
2	Name Plate	Aluminum	
3	Handwheel	Cast Iron	ASTM A126, Class B
4	Stem	Brass	ASTM B16
5	Yoke Bushing	Cast Bronze	ASTM B62
6	Bonnet	Cast Iron	ASTM A126, Class B
7	Gland Follower Nut	Bronze	
8	Gland Follower Stud	Steel	
9	Gland Follower	Cast Iron	ASTM A126, Class B
10	Packing Gland	Brass	ASTM B16
11	Hex Head Cap Screws	Steel	
12	Packing	Graphite	
13	Body Gasket	Graphite	
14	Swivel Nut or Sleeve	Cast Bronze	ASTM B62
15 ¹	Disc	Cast Iron	ASTM A126, Class B
16	Disc Ring	Cast Bronze	ASTM B62
17	Disc Pilot	Cast Bronze	ASTM B62
18	Seat Ring	Cast Bronze	ASTM B62
19	Body	Cast Iron	ASTM A126, Class B

¹ Sizes through 4" have all bronze discs. Sizes 5" through 8" have cast iron disc with bronze disc face rings.

DIMENSIONS - INCHES/MILLIMETERS

Units	Size	A	B	C	D	E	C _v
Inches mm	2 1/2	11.50 292	13.56 345	8.00 20	7.50	1.00	70
Inches mm	3	12.50 318	13.88 352	10.00 254	8.25 210	1.13 29	105
Inches mm	4	14.00 356	16.63 422	12.00 305	10.00 254	1.25 32	195
Inches mm	6	17.50 445	26.25 667	12.00 305	12.50 318	1.44 37	465

† Non-Shock

Note: Does not meet Senate Law S.3874

Accurate as of 5/25/17. For the most current information access www.milwaukeevalve.com