



UP105 1/4"-2"



Bronze Gate Valve For Potable Water
300 psig WOG †
Solid Wedge Disc • Non-Rising Stem
Threaded Bonnet • Threaded Ends

Dimensions and Workmanship Conform to MSS SP-80

MATERIALS LIST


ITEM	PART	MATERIALS	ASTM SPEC.
1	Body	Bronze	B584 C89833
2	Bonnet	Bronze	B584 C89833
3	Wedge	Bronze	B584 C89833
4	Stem	Brass	B21 C46400, H02
5	Stuff Nut	Brass	B283 C37700
6	Check Nut	Brass	B283 C27450
7	Gland ¹	Brass	B283 C37700
8	Wheel Nut	Brass	Commercial
9	Handwheel	Mall. Iron	Commercial
10	Packing	Graphite	Commercial
11	Name Plate	Sh. Alum	Commercial

¹ Not used on 1/2" and smaller

DIMENSIONS

Units	Size	A	B	C	Cv
INCHES	1/4	1.75	3.63	2.00	5.6
mm		44	92	51	
INCHES	3/8	1.81	3.63	2.00	10.7
mm		46	92	51	
INCHES	1/2	2.00	3.63	2.00	17.6
mm		51	92	51	
INCHES	3/4	2.13	4.38	2.50	32.0
mm		54	111	64	
INCHES	1	2.56	5.00	2.75	54.0
mm		65	127	70	
INCHES	1 1/4	2.78	5.31	3.13	97.0
mm		71	135	79	
INCHES	1 1/2	2.81	6.34	3.50	135.0
mm		71	161	89	
INCHES	2	3.31	7.44	3.75	230.0
mm		84	189	95	

† Non-Shock



Note: Lead free refers to the wetted surface of the pipe, fittings and fixtures in potable water systems that have a weighted average lead content $\leq 0.25\%$. Source: California Health and Safety Code (116875).

Accurate as of 5/25/17. For the most current information access www.milwaukeevalve.com

