

DRY CHEMICAL FIRE EXTINGUISHERS

MODEL	A02VB	AA05-1/AA05VB-1	A05/A05VB	PK05	C05
Extinguisher Part No.	429101	434732/ 434735	429001/ 429102	429008 429102	429014
Bracket Part No.	24610	429146	429146	429146	429146
Agent Capacity	2-1/2 lbs. (1.13 kg) FORAY	5 lbs. (2.27 kg) FORAY	5 lbs. (2.27 kg) FORAY	5 lbs. (2.27 kg) Purple-K	5 lbs. (2.27 kg) PLUS-FIFTY C
UL Rating	1-A:10-B:C	3-A:40-B:C	3-A:10-B:C	60-B:C	40-B:C
U. S. Coast Guard Classification	Type B, C, Size I	Type A, Size II Type B, C, Size I	Type A, Size II Type B, C, Size I	Type B, C, Size I	Type B, C, Size I
Discharge Time	9 seconds	14 seconds	14 seconds	17 seconds	14 seconds
Maximum Effective Range	11 ft. (3.4 m)	14 ft. (4.3 m)	14 ft. (4.3 m)	16 ft. (4.9 m)	16 ft. (4.9 m)
Operating Temperature Range	-40°F to 120°F (-40°C to 49°C)	-65°F to 120°F (-54°C to 49°C)	-65°F to 120°F (-54°C to 49°C)	-65°F to 120°F (-54°C to 49°C)	-65°F to 120°F (-54°C to 49°C)
Charged Weight (with Agent)	5 lbs. (2.27 kg)	9 lbs., 14 oz. (4.15 kg)	9 lbs., 14 oz. (4.15 kg)	9 lbs., 14 oz. (4.15 kg)	9 lbs., 14 oz. (4.15 kg)
Height	14-1/4" (362 mm)	17" (432 mm)	17" (432 mm)	17" (432 mm)	17" (432 mm)
Width	5-1/2" (140 mm)	8-1/2" (216 mm)	8-1/2" (216 mm)	8-1/2" (216 mm)	8-1/2" (216 mm)
Depth	3-3/8" (86 mm)	4-7/16" (113 mm)	4-7/16" (113 mm)	4-7/16" (113 mm)	4-7/16" (113 mm)
All models UL Listed; DOT Approved; USCG Approved (only with proper bracket); NOTE: VB denotes with vehicle bracket					
Hydrostatic Test Requirement: Once Every 12 Years					

AA20-1



MODEL	AA10S	PK10S	C10S	AA20-1	PK20	C20
Extinguisher Part No.	436500	436494	436497	434747	429011	429017
Bracket Part No.	435793	435793	435793	30937	30937	30937
Agent Capacity	10 lbs. (4.54 kg) FORAY	10 lbs. (4.54 kg) Purple-K	10 lbs. (4.54 kg) PLUS-FIFTY C	20 lbs. (9.07 kg) FORAY	20 lbs. (9.07 kg) Purple-K	20 lbs. (9.07 kg) PLUS-FIFTY C
UL Rating	4-A:80-B:C	80-B:C	60-B:C	10-A:120-B:C	120-B:C	80-B:C
U. S. Coast Guard Classification	Type A, Size II Type B, C, Size II	Type B, C, Size II	Type B, C, Size II	Type A, Size II Type B, C, Size III	Type B, C, Size III	Type B, C, Size III
Discharge Time	21 seconds	22 seconds	19 seconds	28 seconds	30 seconds	21 seconds
Maximum Effective Range	20 ft. (6.1 m)	20 ft. (6.1 m)	16 ft. (4.9 m)	22 ft. (6.7 m)	22 ft. (6.7 m)	22 ft. (6.7 m)
Operating Temperature Range	-65°F to 120°F (-54°C to 49°C)	-65°F to 120°F (-54°C to 49°C)	-65°F to 120°F (-54°C to 49°C)	-40°F to 120°F (-40°C to 49°C)	-40°F to 120°F (-40°C to 49°C)	-40°F to 120°F (-40°C to 49°C)
Charged Weight (with Agent)	17 lbs., 0 oz. (7.73 kg)	17 lbs., 14 oz. (8.13 kg)	17 lbs., 14 oz. (8.13 kg)	32 lbs., 2 oz. (14.60 kg)	32 lbs., 2 oz. (14.60 kg)	32 lbs., 2 oz. (14.60 kg)
Height	20-1/2" (520 mm)	20-1/2" (520 mm)	20-1/2" (520 mm)	22-1/2" (572 mm)	22-1/2" (572 mm)	22-1/2" (572 mm)
Width	8-1/4" (210 mm)	8-1/4" (210 mm)	8-1/4" (210 mm)	9-1/2" (241 mm)	9-1/2" (241 mm)	9-1/2" (241 mm)
Depth	5-1/4" (135 mm)	5-1/4" (135 mm)	5-1/4" (135 mm)	7-7/32" (183 mm)	7-7/32" (183 mm)	7-7/32" (183 mm)
All models UL Listed; DOT Approved; USCG Approved (only with proper bracket)						
Hydrostatic Test Requirement: Once Every 12 Years						

Operating Pressure: 195 psi (13.4 bar)

FIRE PROTECTION SERVICE INC.

FPS-HOUSTON

Ph: 713-924-9600

Fx: 713-923-6272

FPS-NEW ORLEANS

Ph: 504-466-8003

Fx: 504-469-9922

FPS-CORPUS CHRISTI

Ph: 361-289-9102

Fx: 361-289-1421



Serving the marine and offshore industries since 1952

sales@fps-usa.com • www.fps-usa.com