

DRY CHEMICAL FIRE EXTINGUISHERS

MODEL	I-10-G-1	I-A-10-G-1	I-K-10-G
Extinguisher Part No.	434530	418247	418249
Bracket Part No.	30886	30886	30886
Agent Capacity	10 lbs. (4.5 kg) PLUS-FIFTY C	8.5 lbs. (3.7 kg) FORAY	9 lbs. (4.1 kg) Purple-K
UL Rating	40-B:C	4-A:40-B:C	60-B:C
U. S. Coast Guard Classification	Type B:C, Size II	Type A, Size II Type B:C, Size I	Type B:C, Size II
Discharge Time	15 seconds	15 seconds	19 seconds
Maximum Effective Range	21 ft. (6.4 m)	17 ft. (5.2 m)	25 ft. (7.6 m)
Charged Weight (with agent)	22 lbs. (10.0 kg)	20.5 lbs. (9.3 kg)	21 lbs. (9.5 kg)
Extinguisher Dimensions	16.1" H x 8.3" W x 5.3" D (40.9 x 20.9 x 13.3 cm)		
All models UL and FM Listed; USCG Approved (only with proper bracket)			
Hydrostatic Test Requirement: Once Every 12 Years			

I-A-10-G-1



MODEL	I-20-G-1	I-A-20-G-1	I-K-20-G	I-30-G-1	I-A-30-G-1	I-K-30-G
Extinguisher Part No.	434537	416305	416309	435178	435151	418264
Bracket Part No.	30759	30759	30759	30889	30889	30889
Agent Capacity	20 lbs. (9.1 kg) PLUS-FIFTY C	17 lbs. (7.7 kg) FORAY	18 lbs. (8.2 kg) Purple-K	30 lbs. (13.6 kg) PLUS-FIFTY C	25 lbs. (11.3 kg) FORAY	27 lbs. (12.3 kg) Purple-K
UL Rating	60-B:C	6-A:60-B:C	80-B:C	80-B:C	10-A:80-B:C	120-B:C
U. S. Coast Guard Classification	Type B:C, Size III	Type A, Size II Type B:C, Size II	Type B:C, Size III	Type B:C, Size IV	Type A, Size II Type B:C, Size III	Type B:C, Size IV
Discharge Time	22 seconds	22 seconds	21 seconds	32 seconds	26 seconds	27 seconds
Maximum Effective Range	24 ft. (7.3 m)	20 ft. (6.1 m)	30 ft. (9.1 m)	23 ft. (7.0 m)	20 ft. (6.1 m)	30 ft. (9.1 m)
Charged Weight (with agent)	38 lbs. (17.2 kg)	35 lbs. (15.9 kg)	36 lbs. (16.3 kg)	54.5 lbs. (24.7 kg)	49.5 lbs. (22.5 kg)	51.5 lbs. (23.4 kg)
Extinguisher Dimensions	20.5" H x 10.4" W x 7.0" D (52.1 x 26.4 x 17.8 cm)			22.5" H x 11.1" W x 8.0" D (57.2 x 28.3 x 20.3 cm)		
All models UL and FM Listed; USCG Approved (only with proper bracket)						
Hydrostatic Test Requirement: Once Every 12 Years						

CARBON DIOXIDE FIRE EXTINGUISHERS with Aluminum Shell

MODEL	CD05A-1	CD10A-1	CD15A-1
Extinguisher Part No.	431553	431554	431555
Bracket Part No.	25419	79456	79456
Agent Capacity CO ₂	5 lbs. (2.3 kg)	10 lbs. (4.5 kg)	15 lbs. (6.8 kg)
UL Rating	5-B:C	10-B:C	10-B:C
U. S. Coast Guard Classification	Type B:C, Size I	Type B:C, Size I	Type B:C, Size II
Discharge Time	10 seconds	10 seconds	11 seconds
Maximum Effective Range	6 ft. (1.8m)	6 ft. (1.8m)	6 ft. (1.8m)
Charged Weight (with agent)	13-1/2 lbs. (6.1 kg)	26-3/4 lbs. (12.1 kg)	35-3/4 lbs. (16.2 kg)
Height	19" (48.3 cm)	21-1/4" (54.0 cm)	28" (71.1 cm)
Width	7-1/4" (18.4 cm)	10-15/16" (27.8 cm)	10-15/16" (27.8 cm)
Depth	5-11/32" (13.6 cm)	7" (17.8 cm)	7" (17.8 cm)
All models UL Listed; USCG Approved (only with proper bracket)			
Hydrostatic Test Requirement: Once Every 5 Years			

CD10A-1



FIRE PROTECTION SERVICE INC.

FPS-HOUSTON
Ph: 713-924-9600
Fx: 713-923-6272
FPS-NEW ORLEANS
Ph: 504-466-8003
Fx: 504-469-9922
FPS-CORPUS CHRISTI
Ph: 361-289-9102
Fx: 361-289-1421
FPS-USA

 Serving the marine and offshore
industries since 1952

sales@fps-usa.com • www.fps-usa.com