

PERKO, INC.

## Navigation Lights

For Use On Vessels Over 20 Meters (65.6 ft.) in Length



Fig. 1369  
All-Round Light



Fig. 1370  
All-Round Light



Fig. 1372  
Side Light



Fig. 1373  
Masthead Light



Fig. 1374  
Stern Light

### Black Plastic

Complete with a pre-wired medium prefocus socket and one (double lens navigation lights come with two) 3-foot length of 16/3-SO cable through a watertight terminal tube. Watertight access cap for rebulbing and cleaning. Bulb not included.

### Spare Parts Ordering Information

Cat. No.	Item
1363000BLK	Access Cap Assembly
0367	Medium Prefocus Socket

Height Overall Inches	Height Lens Inches	Mounting Bolt Size Inches	Weight Pounds
9-1/4	6-3/4	3/8	5-1/8



## Single Lens Navigation Lights

Description	Visibility Arc	Visibility Miles	Single Stack Cat. No.
Red Side Light	112-1/2°	3	1372RE0BLK
Green Side Light	112-1/2°	3	1372GE0BLK
White Masthead Light	225°	6	1373E00BLK
White Stern Light*	135°	3	1374E00BLK
Yellow Towing Light	135°	3	1374ME0BLK
White All-Round Light*	360°	3	1369E00BLK
White All-Round Light**	360°	6	1369HE0BLK
Red All-Round Light	360°	3	1370RE0BLK
Green All-Round Light	360°	3	1370GE0BLK
Yellow All-Round Light	360°	3	1370ME0BLK

Special lights to meet local requirements are available upon request.

\* These lights are supplied with a Gray Tinted Lens. \*\* For Great Lakes use.



## Double Lens Navigation Lights



Fig. 1364  
Side Light



Fig. 1365  
Masthead Light



Fig. 1366  
Towing Light



Fig. 1367  
All-Round Light

### Important Bulb Data

To comply with U.L. Standard 1104, the lights listed on this page must be used with the following PERKO bulbs:

#### Required Bulbs

24V – Cat. No. **0342024CLR**      120V – Cat. No. **0342004CLR**  
 120V – Cat. No. **0342RS4CLR**      220V – Cat. No. **0342220CLR**  
 (when a "Rough Service" bulb is required)

Height Overall Inches	Height Lens Inches	Mounting Bolt Size Inches	Weight Pounds
17-1/4	6-3/4	3/8	10-1/2

Description	Visibility Arc	Visibility Miles	Single Stack Cat. No.
Red Side Light	112-1/2°	3	1364RE0BLK
Green Side Light	112-1/2°	3	1364GE0BLK
White Masthead Light	225°	6	1365E00BLK
White Stern Light	135°	3	1366E00BLK
Yellow Towing Light	135°	3	1366ME0BLK
White All-Round Light*	360°	3	1367E00BLK
White All-Round Light**	360°	6	1367HE0BLK
Red All-Round Light	360°	3	1368RE0BLK
Green All-Round Light	360°	3	1368GE0BLK
Yellow All-Round Light	360°	3	1368ME0BLK

Special lights to meet local requirements are available upon request.

\* These lights are supplied with a Gray Tinted Lens. \*\* For Great Lakes use.

