

EATON CROUSE-HINDS PAULUHN

## ARCHITECTURAL EXIT SIGNS FLUORESCENT OR INCANDESCENT ABS

**CONSTRUCTION:** The housing and the diffuser frame are made of corrosion resistant aluminum with a polyester powder coated finish.

**LAMP TYPE:** The fluorescent model has one 8W T5 cool white lamp (included). The incandescent model has one 25W T6 lamp (included).

**DIFFUSER:** The polished acrylic diffuser panel is double sided with red "EXIT" letters. Color of letters and background can be found in the catalog chart.

**REFLECTOR:** Aluminum with a white high gloss polyester powder coat finish for the fluorescent model and highly specular ALZAK aluminum for the incandescent version.

**BALLAST:** A low power factor 120V 60 Hz ballast is provided for fluorescent model.

F1ACFGWEXERAL

**OPTIONS:**

**Ballasts:** Emergency ballast available for fluorescent only.

**Diffuser:** Standard language is English. Please specify other language.

### CATALOG CHART

1 2 3 4 5 6 7 8

**1 I** = incandescent  
F = fluorescent

**3 Material**  
A = Aluminum

**5 Letters/Background**  
RW = red on white

**7 EM** = Emergency Ballast

**2 Number Of Faces**  
1 = single face  
2 = double face

**4 Mounting**  
W = wall  
C = ceiling  
WF = wall recessed  
CF = ceiling recessed

**6 Arrow Direction**  
BLANK = no arrow  
EXER = emergency exit

**8 Input Voltage**  
BLANK = 120V 60 Hz  
226 = 220V 60 Hz  
225 = 220V 50 Hz  
276 = 277V 60 Hz

## FLUORESCENT EXIT LIGHTS ABS

**CONSTRUCTION:** A corrosion resistant aluminum housing with a high gloss polyester powder coated finish and a white ABS cover. By loosening four captive knurled thumb screws, the cover can be removed permitting easy relamping.

**LAMP TYPE:** Two cool white T5 8W fluorescent lamps are standard.

**LENS:** The unit has two lenses with "EXIT" in red letters on a translucent white background.

**REFLECTOR:** Aluminum with a high gloss white polyester powder coated finish.

**BALLAST:** A low power factor 120V 60 Hz ballast.

**MOUNTING:** The unit can be ordered for surface or flush mounting, either vertically or horizontally for wall or ceiling. A pendant model, normally drilled & tapped 1/2" N.P.T. (1" max.) is also available. The pendant model cannot be furnished with vertical lettering.

**OPTIONS:**

**Ballasts:** Emergency ballasts and 220V 60 Hz are also available.

**Lens:** Standard language is English. Please specify other language.



F1703F



F1704F

Description	Weight	Surface Mount	Flush Mount	Pendant Mount
Horizontal Lettering	5.5 lbs. (2.50 kg)	F1703	F1703F	F1705
Vertical Lettering	5.5 lbs. (2.50 kg)	F1704	F1704F	—