

EATON CROUSE-HINDS PAULUHN

## CORD CONNECTOR & PLUG – PIN & SLEEVE TYPE


### U.S.C.G. Accepted, U.L. 498, Plugs and Receptacles

**CONSTRUCTION:** ABS high impact plastic, a series of plug and cord connectors that are suited for corrosive saltwater areas as well as petro-chemical operations. The standard threaded thermoplastic plug and connector, which are interchangeable with existing equipment, are yellow colored to meet O.S.H.A. requirements.

**RATINGS:** 20 amp 600V AC, 2 pole 3 wire, 3 pole 4 wire. Specify voltage as a suffix.

Description	Catalog No. Plug Only Male End	Catalog No. Female End	Catalog No. Complete Cord Connector
2 Pole 3 Wire	*420PP	422FC	426PC
3 Pole 4 Wire	*420-4PP	423-FC	426-4PC

\* Available in reverse service. Add suffix "RS" to catalog number.





## VAPOR & WATERPROOF FIXTURES INCANDESCENT & COMPACT FLUORESCENT

### 30° Angle Reflector Surface or Bulkhead Mount U.L. 1598A Marine—U.S.C.G. Accepted

### 60 – 300W Incandescent or 13, 18, 26 and 32W Fluorescent

Cat. No.	A	B
1729BM	10-3/4"	11-1/4"
1729BQ	11"	11-1/4"
1729BM7	10-3/4"	11-1/4"
1729BQ7	11"	11-1/4"
1731BM8	11-7/8"	14-1/2"
1731BQ8	12-1/8"	14-1/2"
1731BM	11-7/8"	14-1/2"
1731BQ	12-1/8"	14-1/2"



**CONSTRUCTION:** Heavy-duty wall cast brass or copper-free marine grade aluminum.

**OUTLETS:** Standard is undrilled. Available up to maximum of 1" N.P.T. fourway.

**REFLECTORS:** Fiberglass, polyester reinforced up to 100W. ABS reflectors for higher wattages.

**LAMPHOLDER:** Phenolic with nickel-plated copper screw shell.

#### OPTIONS:

**Lampholder:** Porcelain available, add suffix P. Shock and vibration proof available on all lampholders, add suffix SP.

**Terminal Block:** Add suffix "T" for a 4 wire block (Cat. No. CX3070), add suffix "T6" for a 6 wire block (Cat. No. CX3076).

**Globe:** Clear glass globe is standard. For color globes add suffix "RED", "BLU", "GRN", or "YEL".

Lamp	Globe	Bronze Weight	Bronze Cat. No.	Junction Box	Depth	Guard	Aluminum Cat. No.	Junction Box	Depth	Guard	Lamp Holder
100W	INX 2006CLR	11 lbs. (5 kg)	1729BM	INX 6037B	2"	INX 1036B	1729AM	INX 6037A	2"	INX 1036A	INX 4000
	6"	12 lbs. (5.45 kg)	1729BQ	INX 6057B	2-1/4"	6"	1729AQ	INX 6057A	2-1/4"	6"	
150W	INX 2007CLR	11 lbs. (5 kg)	1729BM7	INX 6037B	2"	INX 1037B	1729AM7	INX 6037A	2"	INX 1037A	INX 4000
	7"	12 lbs. (5.45 kg)	1729BQ7	INX 6057B	2-1/4"	7"	1729AQ7	INX 6057A	2-1/4"	7"	
150W-200W A-23	INX 2008CLR	14 lbs. (6.36 kg)	1731BM8	INX 6037B	2"	INX 1038B	1731AM8	INX 6037A	2"	INX 1038A	INX 4028
	8"	15 lbs. (6.81 kg)	1731BQ8	INX 6057B	2-1/4"	8"	1731AQ8	INX 6057A	2-1/4"	8"	
200W-300W	INX 2009CLR	14 lbs. (6.36 kg)	1731BM	INX 6037B	2"	INX 1020B	1731AM	INX 6037A	2"	INX 1020A	INX 4000
	9"	15 lbs. (6.81 kg)	1731BQ	INX 6057B	2-1/4"	9"	1731AQ	INX 6057A	2-1/4"	9"	

#### Compact Fluorescent Lamps

The 13, 18, 26 or 32 compact fluorescent lamps will fit the 7" units. To order, begin with the prefix "F" to the Cat. No., then add suffix "13", "18", "26" or "32".

**For example:** F1729BM-26

Incandescent	Compact Fluorescent
60W	= 13W
75W	= 18W
100W	= 26W
150W	= 32W

Based on 120V 60 Hz as standard; 277V 60 Hz is also available.

**Crouse-Hinds**  
by **EATON**