

EATON CROUSE-HINDS PAULUHN

INSIDE DRIP PROOF TYPE INTERIOR DECORATIVE RECESSED LUMINAIRES



APPROVALS: UL 1598A - Marine Inside Drip Proof Type, ABS, Insulation Contact (IC) rated for contact with noncombustible mineral wool insulation and Conforms to IP 45 with a sealed diffuser. Zinc coated steel with

oven-cured polyester powder coat protective finish maximizes corrosion resistance. Housing is provided with two, 1/2" or 3/4" NPT knockouts, which will accommodate European M20 and M25

hubs. Standard housing color is white, custom colors are available. Trim rings are white as standard, but custom colors, chrome and marine brass finishes are available. Trim rings are also available with stand-off or sealed diffusers. Sealed diffusers available on compact fluorescent to 18W, Halogens or incandescent "A" Type lamp to 60W maximum. 3 pole terminal block installed as standard on all models. Compact fluorescent & incandescent luminaires will include a highly specular aluminum silver reflector as standard. LED and MR-16 type luminaires are provided with lamps. Compact fluorescent, halogen par and incandescent luminaires are not provided with lamps. Standard luminaires equipped with a compact fluorescent 120V 60 Hz electronic ballast.

Ordering Sample

1. DLF 2. 26 3. -276

(1, 2, & 3) Model, Wattage, and Ballast

(If 3 is blank = 120V 60 Hz)

Compact Fluorescent lamp	DLF
13 Watt	13
18 Watt	18
26 Watt	26
32 Watt	32
220V 50 Hz	-225
220V 60 Hz	-226
277V 60 Hz	-276
Halogen, Par lamp	DLH
50 Watt	50
60 Watt	60
75 Watt	75
100 Watt	10
Incandescent	DLI
100 Watt	10
LED DLL	
14 Watt	14
Halogen, MR-16 lamp	DLM
50 Watt	50
75 Watt	75
220-240V 50/60 Hz	-225

(4-7) Options per model may be added as available.

Options:

For all models except LED:

- Marine brass finish trim ring B
- Chrome plated trim ring C
- Trim ring with Glass diffuser D
- *Sealed diffuser on trim ring (conforms to IP 45) S
- Frosted center, clear edge F
- Clear center, frosted edge H

*Compact Fluorescent to 18W, Halogens to 60W or incandescent "A" Type lamp.

For Compact Fluorescent lamp:

- | | |
|---|-------|
| Dimmable Ballast (not available for 13W) | DIM* |
| • Gold finish reflector | G |
| • Red DR acrylic diffuser (26 Watt max) | RV |
| • Blue Lens - Night Vision Compatible (26 Watt max) | BV |
| • Trim ring with Polycarbonate diffuser | X |
| • 220V 50 Hz | -225* |
| • 220V 60 Hz | -226* |
| • 277V 60 Hz | -276* |
| • Radio Interference Filter | RFI |

*Not all wattages available with dimmable ballast in optional voltages.

Halogen MR-16 lamp:

- 220-240V 50/60 Hz -225

Incandescent lamp:

- Gold finish reflector G

INSIDE DRIP PROOF CEILING FIXTURE



F1143

HOUSING: Corrosion resistant brass or copper-free aluminum with an oven-cured polyester powder coat protective finish. Stainless steel hardware.

APPROVALS: UL 1598A (Marine Inside Drip Proof Type) and ABS. Conforms to IP52.

KNOCKOUTS: one 3/4" N.P.T.

LENS: Prismatic polycarbonate lens.

GASKETS: One piece neoprene gasket.

MOUNTING: Fits a 4" stamp steel or cast junction box.

VOLTAGE: Rated for operation on 120V AC 60 Hz as standard. For 220V 60 Hz, add -226 suffix to part number below. For 277V 60 Hz, add -276.

BALLAST: High power factor (HPF) electronic ballast.

DIMENSIONS: 12-1/4" square. 3" high. **WEIGHT:** 6 lbs.

Lamp Type	Lamp Size	Brass	Aluminum
2PIN GX23	2 x 13W	F1143B-13	F1143A-13
2PIN G24D	2 x 18W	F1143B-18	F1143A-18
2PIN G24D	2 x 26W	F1143B-26	F1143A-26

Crouse-Hinds
by **EATON**