

EATON CROUSE-HINDS PAULUHN

FLUORESCENT WATERTIGHT OVERHEAD LIGHTING

Available in one, two and three lamp units (35W & 60W fixtures available in one and two only). Compact fluorescent fixtures available in two and four lamp 40W versions. The fixture is watertight.



FPS - Fiber Glass

HOUSING: Glass reinforced polyester with a natural grey finish.



FAS - Aluminum Housing

HOUSING: Aluminum with a polyester powder coated finish.



FSS - Stainless Steel

HOUSING: Stainless steel with a natural finish.

Description	No. of Lamps	Lamp Type	FPS	FAS	FSS
17W Rapid Start 265 MA 24" Lamp	1 2 3	F17T8	FPS117 FPS217 FPS317	FAS117 FAS217 FAS317	FSS117 FSS217 FSS317
20W Trigger Start 24" Lamp	1 2 3	F20T12	FPS120 FPS220 FPS320	FAS120 FAS220 FAS320	FSS120 FSS220 FSS320
32W Rapid Start 265 MA 48" Lamp	1 2 3	F32T8	FPS132 FPS232 FPS332	FAS132 FAS232 FAS332	FSS132 FSS232 FSS332
35W High Output 800 MA 24" Lamp	1 2 3	F24T12/HO	FPS135 FPS235 N/A	FAS135 FAS235 N/A	FSS135 FSS235 N/A
40W Rapid Start 430 MA 48" Lamp	1 2 3	F40T12	FPS140 FPS240 FPS340	FAS140 FAS240 FAS340	FSS140 FSS240 FSS340
60W High Output 800 MA 48" Lamp	1 2 3	F48T12/HO	FPS160 FPS260 N/A	FAS160 FAS260 N/A	FSS160 FSS260 N/A
40W Single Ended Compact Fluorescent	2 4	F40W/2G11	FPSC240 FPSC440	FASC240 FASC440	FSSC240 FSSC440
SSW Single Ended Compact Fluorescent	2 4	F55W/2G11	FPSC255 FPSC455	FASC255 FASC255	FSSC255 FSSC455

LATCHES: Over the center stainless steel cam latches.

REFLECTOR: White powder coated aluminum.

OUTLETS: All units are supplied with two 3/4" NPT outlets, one plugged, providing a through-feed service where required.

GASKETS: One continuous piece extruded neoprene gasket provides an effective seal between the lens and housing.

LAMPHOLDER: Spring loaded lampholders provide a positive contact and maximum resistance to shock and vibration.

BALLAST: An HPF120V 60Hz ballast is supplied as standard.

LAMP TYPE: All fixtures other than compact fluorescent types are supplied without lamps. Compact fluorescent versions are available in two lamp and four lamp 40W fixtures.

LENS: High impact polycarbonate lens. Optional matte acrylic also available.

OPTIONS: Phenolic Terminal Block, Access Plate, Clear Polycarbonate Drop Lens, Emergency Ballast, 220V 50Hz, 220V 60Hz and 277V 60Hz Ballasts, Water Tight at zero degrees.



154 27th Street, Brooklyn, NY 11232

www.manning-electric.com

Stocking Distributor
Pauluhn products

TradeNet ID 53046

Crouse-Hinds
by **EATON**

Tel: (718) 832-2488 • Fax: (718) 832-2493