


EATON CROUSE-HINDS PAULUHN

## FLUORESCENT BERTH & MIRROR LIGHTS

Surface Mount, U.S.C.G. Accepted,  
U.L. Listed 1570 Fluorescent,  
120VAC or 220VAC  
1 or 2 – 15W Lamp



1 Lamp—F115 2 Lamp—F215

**CONSTRUCTION:** Marine-grade aluminum, corrosion-resistant housing with a polyester powder coated finish.

**DIFFUSER:** Clear prismatic lens, high impact or acrylic.

**REFLECTOR:** Aluminum with a white high gloss polyester powder coated finish.

**BALLAST:** High power factor, rapid start supplied standard. Can be supplied with low power factor on request.

**SWITCH:** A push type momentary contact switch is provided as standard. Double pole toggle type switch is optional.

**LAMPS:** One or two 15W lamp. Lamps not included.

**CONVENIENCE OUTLET:** A 125V 3 wire 2 pole "U" ground outlet is provided as standard.

**MOUNTING:** 2-1/4" mounting holes in back of fixture.

**DIMENSIONS:** 21-1/4" long, 5-1/2" high, 5-1/2" wide.

**VOLTAGE:** Specify 120VAC or 220VAC.

U.L. 1598A Inside Type U.S.C.G.



**CONSTRUCTION:** The body is made of extruded copper-free marine-grade aluminum, with an oven cured polyester powder coated white gloss protective finish.

**DIFFUSER:** The lens is extruded clear, high impact DR acrylic, fluted.

**REFLECTOR:** The reflector is aluminum, matte finished.

**BALLAST:** The ballast for the FBL18 is low power factor, pre-heat type, momentary contact, 120V 60 Hz. The ballast for the FBL117 is an electronic ballast type, 120V 60 Hz.


**SWITCH:** The switch is an on/off push button type, momentary contact.

**LAMPS:** Supplied with one or two 8W T5 fluorescent lamps (FBL18) or one 17W T8 fluorescent lamp (FBL117).

**KNOCKOUTS:** One 3/4" and one 1/2" knockouts are provided on the back.

Description	Lamp Size	Aluminum Cat. No.
Berth & Mirror Light	(1)-8WT5	<b>FBL18</b>
	(2)-8WT5	<b>FBL28</b>
Berth & Mirror Light	(1)-17WT8	<b>FBL117</b>

Flush or Surface Mount, Vertical or Horizontal  
U.S.C.G. Accepted, U.L. Listed 1570 Fluorescent  
120VAC or 220VAC  
2 – 8W Lamp

1 Lamp—FBN18  
2 Lamp—FBN281 Lamp—FMN18  
2 Lamp—FMN28

**CONSTRUCTION:** Corrosion-resistant aluminum housing.

**OUTLETS:** All units supplied with one 1/2" and 3/4" KO.

**REFLECTOR:** Aluminum with a white high gloss polyester powder coated finish.

**LENS:** A high impact fluted acrylic lens provided.

**BALLAST:** Low power factor, pre-heat supplied standard.

**SWITCH/STARTER:** Push type momentary contact.


**LAMPS:** Two 8W fluorescent lamps. Lamps are included.

**DIMENSIONS:** 14-3/8" long, 4-1/4" high, 3-1/2" wide.

**VOLTAGE:** 120VAC 60 Hz standard.

Surface Mount, U.S.C.G. Accepted  
U.L. Listed 1570 Fluorescent,  
120VAC or 220VAC  
1-15W Lamp

F1061



**CONSTRUCTION:** Corrosion-resistant aluminum with a powder coated anodized type finish.

**SHADE:** An adjustable shade is provided.

**SWITCH/STARTER:** A double pole rocker is provided.

**CONVENIENCE OUTLET:** A 125V 2 wire 3 pole "U" ground supplied standard. Can be furnished less outlet on request.

**VOLTAGE:** Specify 120VAC or 220VAC.

**OVERALL DIMENSIONS:** 19-1/4" long x 3" wide x 5-5/8" deep.