

EATON CROUSE-HINDS PAULUHN

## FLUORESCENT DESK & CHART LAMPS

Surface or Bulkhead Mount, Two Lamps U.L. Marine-U.S.C.G.—120VAC or 220VAC



FE215/1  
Bulkhead Mount  
Stationary Arm



FE215/2  
Bulkhead Mount  
Single Adjustable Arm



FE215/3  
Bulkhead Mount  
No Arm, No Neck



FE215/4  
Bulkhead Mount  
Double Adjustable Arm

**CONSTRUCTION:** Corrosion resistant housing in aluminum sheet metal.

**LENS:** A clear high impact acrylic lens is supplied with 15W units.

**REFLECTOR:** Aluminum with a white, high gloss polyester powder coating.

**BALLAST:** High power factor 120V 60 Hz is standard.

**SWITCH:** A double pole toggle on the junction box is standard.

**LAMP TYPE:** Two 8W or 15W fluorescent lamps used. Not included.

Description	Lamp Size	Alum. Weight	Alum. Cat. No.
Stationary Arm	1-15W	12 lbs. (5.5 kg)	FE28/1
	2-15W		FE215CV/1
Single Adjustable Arm	1-15W	12 lbs. (5.5 kg)	FE28/2
	2-15W		FE215CV/2
No Arm, No Neck	1-15W	12 lbs. (5.5 kg)	FE28/3
	2-15W		FE215CV/3
Double Adjustable Arm	1-15W	12 lbs. (5.5 kg)	FE28/4
	2-15W		FE215CV/4

### OPTIONS:

**Diffuser:** For a flat clear high-impact polycarbonate lens, add suffix "CV". Add suffix "RV" for a red lens or suffix "YV" for an amber lens.

**Ballast:** Optional 220V 60 Hz available.

**Convenience Outlet:** A 125W 3W 2P "U" ground available, add suffix "CO" to catalog number.

**Arm Types:** Stationary arm (6-3/8") and adjustable arms.

## FLUORESCENT DESK LAMPS

U.L. Marine-U.S.C.G. 2 – 15W Lamp



FE215CV/5  
Double Stationary Arm



FE215CV/6  
Double Adjustable Arm

**CONSTRUCTION:** Corrosion resistant aluminum with a powder coated anodized type finish.

**REFLECTOR:** Aluminum with a white high gloss polyester powder coated finish.

**LAMP TYPE:** Two 15W fluorescent lamps, not included.

**MOUNTING:** The base is surface mounted by threaded studs.

**SWITCH/STARTER:** A push type momentary contact switch is mounted on the reflector shade. A double pole toggle switch is optional.

**CORD & PLUG:** A three conductor, SJT cord and molded plug.

**LENS:** A clear high impact acrylic lens is supplied.

### OPTIONS:

**Diffuser:** A diffuser is not provided on the standard unit. For a flat clear high-impact polycarbonate lens, add suffix "CV". Add suffix "RV" for a red lens or suffix "YV" for an amber lens.

**Dimensions:** Base—8-3/8" wide; Overall—13-1/4" high x 18-1/2" wide.

## INCANDESCENT TABLE LAMP

U.L. 1571 MARINE-U.S.C.G. ABS



1017B

Description	Cat. No.	Weight
Aluminum Table Lamp	1017B	4 lbs.

**CONSTRUCTION:** Robust base in polyester coated steel. Polished brass center column. **SWITCH:** A double pole toggle switch is standard. **LAMP TYPE:** Max. 150W A-21 medium base incandescent lamp. Not included. **SHADE:** White polyplastic belque with taped edgings is standard. **PEDESTAL:** The standard unit is provided with a 4-1/2" square pedestal base. **MOUNTING:** 1/4" threaded pipe and lock nuts are provided for permanent table mounting. **CORD & PLUG:** Provided with an 8', three conductor, SJT cord and molded plug.

**Crouse-Hinds**  
by **EATON**