

EATON CROUSE-HINDS PAULUHN

WATERTIGHT GENERAL ALARM CONTACT MAKER

For Outside and Corrosive Environments

CONSTRUCTION: Cast marine brass or copper-free aluminum with a natural finish. Stainless steel hardware.


APPROVALS: ABS, Type 4X and conforms to IP66.

OUTLETS: All units furnished blank. Can be supplied with up to four 3/4" NPT outlets. Please state requirements when ordering.

SWITCHES: Spring loaded double pole single throw.

VOLTAGE OPERATION: 833 unit is rated for operation on 15 Amp 125V AC, 10 Amp 24V DC or 2 Amp 125V DC. 834 unit is rated for operation on 20 Amp 600V AC, 15 Amp 24V DC or 5 Amp 125V DC.

MOUNTING: Surface or flush mounting. Surface mount units are mounted via two 11/32" Ø mounting holes. Flush mount units are mounted via four 9/32" mounting holes.



833

SPARE PARTS

Boxes

833 Surface Mount	INX6037B
834 Surface Mount	INX6083B
833F Flush Mount	INX6053B
834F Flush Mount	INX6054B

Handle

INX8017B

Cover Gasket

GKT3002

Interiors

833 INX3058



834 INX3118-EP

Cover with Handle

INX6576B

"O" Ring

GKT1041

	Description	Approximate Dimensions	Weight (lbs.)	Marine Brass Type (B)
	15 Amp 120V AC Surface Mount 3 Wire	4-1/2" W x 4-1/2" D x 4-11/32" H	5.0	833
	20 Amp 600V AC Surface Mount 3 Wire	4-1/2" W x 4-1/2" D x 5-11/32" H	6.0	834
	15 Amp 120V AC Flush Mount 3 Wire	5-11/16" W x 5-11/16" D x 4-21/32" H	5.0	833F
	20 Amp 600V AC Flush Mount 3 Wire	5-11/16" W x 5-11/16" D x 4-21/32" H	6.0	834F

EXPLOSION PROOF GENERAL ALARM CONTACT MAKER

CONSTRUCTION: Cast brass with natural finish. Stainless steel hardware.


APPROVALS: U.S.C.G., ABS Type Approved, Hazardous Locations, UL 98, UL 698, Class I, Division 1, Groups C & D, conforms to IP66

OUTLETS: All units furnished with one 1/2" NPT outlet. Can be supplied with up to four 3/4" NPT outlets. Please state requirements when ordering.

SWITCHES: Spring loaded double pole single throw. Locking on position prevents accidental activation. Spring loaded knob retains the lever in the ON position until the knob is pulled and a spring returns the lever to the OFF position.

VOLTAGE OPERATION: EP833 unit is rated for operation on 15 Amp 125V AC, 10 Amp 24V DC or 2 Amp 125V DC. EP 834 unit is rated for operation on 20 Amp 600V AC, 15 Amp 24V DC or 5 Amp 125V DC.

MOUNTING: Surface mounted via four 11/32" Ø mounting holes.



EP833/EP834

SPARE PARTS

Box

INX6040B

Handle

INX8017B


"O" Ring

GKT1041

Interior Switches

EP833 INX3058

EP834 INX3118EP

	Description	Approximate Dimensions	Weight (lbs.)	Marine Brass Type (B)
	15 Amp 120V AC Surface Mount	4-15/16" W x 4-15/16" D x 5-5/8" H	10.0	EP833
	20 Amp 600V AC Surface Mount	4-15/16" W x 4-15/16" D x 5-5/8" H	10.0	EP834



154 27th Street, Brooklyn, NY 11232

www.manning-electric.com

Stocking Distributor
Pauluhn products

TradeNet ID 53046

Crouse-Hinds
by EATON

Tel: (718) 832-2488 • Fax: (718) 832-2493