

CRIMP TERMINALS



Nylon Insulated Ring – Insulation Grip

Cat. No.	Bolt Hole
Pkg. Qty. 100, 22-16 Wire Range, .136 Max. Ins.	
RA18-4	#4
RA18-6	#6
RA18-8	#8
RA18-10	#10
RA18-14	1/4"
RA18-516	5/16"
RA18-38	3/8"
RA18-12	1/2"
Pkg. Qty. 100, 18-14 Wire Range, .162 Max. Ins.	
RB14-4	#4
RB14-6	#6
RB14-8	#8
RB14-10	#10
RB14-14	1/4"
RB14-516	5/16"
RB14-38	3/8"
RB14-12	1/2"
Pkg. Qty. 50, 12-10 Wire Range, .210 Max. Ins.	
RC10-6	#6
RC10-8	#8
RC10-10	#10
RC10-14	1/4"
RC10-516	5/16"
RC10-38	3/8"
RC10-12	1/2"

U.L. Listed E9809



Nylon Insulated Fork – Insulation Grip

Cat. No.	Bolt Hole
Pkg. Qty. 100, 22-16 Wire Range, .136 Max. Ins.	
RA18-6F	#6
RA18-8F	#8
RA18-10F	#10
RA18-14F	1/4"
Pkg. Qty. 100, 18-14 Wire Range, .162 Max. Ins.	
RB14-6F	#6
RB14-8F	#8
RB14-10F	#10
RB14-14F	1/4"
Pkg. Qty. 50, 12-10 Wire Range, .210 Max. Ins.	
RC10-6F	#6
RC10-8F	#8
RC10-10F	#10
RC10-14F	1/4"

U.L. Listed E9809

Installing tools: WT145C, WT2000, WT112M, ERG-2001, ERG-2003, WT145A



Non-Insulated Ring

Cat. No.	Bolt Hole
Pkg. Qty. 25, 9-8-7 Wire Range	
D8-10*	#10
D8-14*	1/4"
D8-516*	5/16"
D8-38*	3/8"
D8-12*	1/2"
Pkg. Qty. 200, 9-8-7 Wire Range	
D10161	#8
D10361	#10
D10711	1/4"
D10721	5/16"
D10731	3/8"
D975*	1/2"
Pkg. Qty. 20, 6-5 Wire Range	
E6-10*	#10
E6-14*	1/4"
E6-516*	5/16"
E6-38*	3/8"
E6-12*	1/2"
Pkg. Qty. 200, 6-5 Wire Range	
E10261	#10
E10711	1/4"
E10721	5/16"
E10731	3/8"
Pkg. Qty. 20, 4-3 Wire Range	
F4-10*	#10
F4-14*	1/4"
F4-516*	5/16"
F4-38*	3/8"
F4-12*	1/2"
Pkg. Qty. 100, 4-3 Wire Range	
F10261	#10
F10711	1/4"
F10721	5/16"
F10731	3/8"

* Not available on Mylar Tape.

Installing tools: ERG-2005 (D Series only)
WT115A,D, E, F & G, TBM6/TBM65, WT3185



Non-Insulated Fork

Cat. No.	Bolt Hole
Pkg. Qty. 100, 22-16 Wire Range	
A18-6F	#6
A18-8F	#8
A18-10F	#10
Pkg. Qty. 100, 18-14 Wire Range	
B14-6F	#6
B14-8F	#8
B14-10F	#10
B14-14F	1/4"
Pkg. Qty. 50, 12-10 Wire Range	
C10-6F	#6
C10-8F	#8
C10-10F	#10
C10-14F	1/4"

U.L. Listed E9809

Installing tools: WT111M, WT112M, WT110M, WT2000, ERG-2002



1 RA18-250F
nylon self-insulated
installing tools – WT145C,
WT2000, ERG-2001,
ERG-2003, WT112M



2 18RA-250F
vinyl self-insulated
installing tools – WT145C,
WT2000, ERG-2001,
ERG-2003, WT112M



3 18RA-2577
nylon fully-insulated
installing tools – WT145C,
WT2000, ERG-2001,
ERG-2003, WT112M



4 RAS18-250AX
heat-shrinkable fully
insulated disconnects
installing tool – WT1255



5 18RA-250T
vinyl self-insulated
installing tools – WT145C,
WT2000, ERG-2001,
ERG-2003, WT112M



6 18RA-251T
nylon fully insulated
installing tools – WT145C,
WT2000, ERG-2001,
ERG-2003, WT112M



7 18RAS-251TX
heat shrinkable nylon fully
insulated
installing tool – WT1255



8 A18-250T
Non-insulated/insulated grip
installing tool – WT110M



9 18-251T
Non-insulated
installing tools – WT110M,
WT111M, WT2000,
WT112M, ERG-2002, WT112M

250 Series – Female Disconnects

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.
1 RA18-250F	100	22-18	.136
RB14-250F	100	16-14	.162
RC10-250F	50	12-10	.215
2 18RA-250F	100	22-18	.150
14RB-250F	100	16-14	.170
10RC-250F	50	12-10	.250
18RA-2577	100	22-18	.165
3 14RB-2577	100	16-14	.185
10RC-2577	50	12-10	.225
4 RAS18-250AX	50	22-18	.170
RBS14-250AX	50	16-14	.200
RCS10-250AX	25	12-10	.250

Material: brass

Finish: tin plated

U.L. Listed E66716

250 Series – Male Tabs

Tab size - .250 x .032

Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.
5 18RA-250T	100	22-18	.150
14RB-250T	100	16-14	.170
10RC-250T	50	12-10	.250
6 18RA-251T	50	22-18	.150
14RB-251T	50	16-14	.170
10RC-251T	25	12-10	.210
7 18RAS-251TX	50	22-18	.170
14RBS-251TX	100	16-14	.200
10RCS-251TX	100	12-10	.250
8 A18-250T	100	22-18	–
B14-250T	100	20-14	–
A18-251T	100	22-18	–
B14-251T	100	16-14	–
C10-251T	50	12-10	–

Material: brass

Finish: tin plated

Installation Tools



WT112M



ERG2001



154 27th Street, Brooklyn, NY 11232

www.manning-electric.com

Stocking Distributor
for Thomas & Betts

TradeNet ID 53046



MIPCO™ Russellstoll®

Tel: (718) 832-2488 • Fax: (718) 832-2493