



MARINE DUCT PRODUCTS

Standard ducting sizes are:
2", 4", 6", 8", 10", 12", 14", 16", 18", 20", 22", 24", 30" & 36".
The range of sizes available for each style is shown below.

GENERAL SERVICE


Neoprene-coated polyester ducting with wire reinforced ducts. Spring-steel wire helix is completely fabric enclosed for flexibility and crush resistance. Flame retardant to UL-94VO. 25 ft. lengths.

Type NP-1 (Single Ply) is an extremely lightweight and flexible hose designed for air, fume control and dust collecting.

Sizes: 2" thru 24" **Temperature Range:** -40°F to 250°F
Compression Ratio: 6:1 **Material:** Polyester/Neoprene

Type NP-2 (Double Ply) has a bi-directional construction which allows two-way flow for all applications requiring air handling, dust and fume control and light material handling.

Sizes: 1-1/2" thru 16" **Temperature Range:** -65°F to 260°F
Compression Ratio: 6:1 **Material:** Polyester/Neoprene



THERMOPLASTIC DUCT General Service

RFH & RFH-W are each a versatile general-purpose hose constructed of thermoplastic rubber reinforced with a wire helix. Both RFH and

RFH-W are highly resistant to chemicals and are capable of handling fumes as tough as MEK, sulfuric acid or toluene. RFH-W has an external wear strip which covers the wire.

RFH / RFH-W – Sizes: 2" thru 20"
Temperature Range: -60°F to 275°F, intermittent service up to 300°F
Compression Ratio: 6:1




DUCT CONNECTOR

Used to couple multiple lengths of ducting. Equal inside diameter on both ends.

Sizes: 4", 6", 8", 10", 12", 14", 16", 18" & 20" **Standard Length:** 5"

FLANGED DUCT CONNECTOR

12" Butterworth Flange: 12.25" I.D.
15.3" bolt circle, 16.8" O.D., 10 bolt x 1" bolt dia.
15" Butterworth Flange: 15.25" I.D.,
20.5" bolt circle, 21.5" O.D., 10 bolt x 1" bolt dia.
For other sizes, please specify flange dimensions.



Star Type: PN 200A-S-20/30A

BRANCH PIPE COUPLINGS

Chrome plated steel branch pipe couplings are available in star type and line type.
Inlet includes: 1 ea. 400 SH, 1 ea. 400 PM.
Outlet includes: 4 ea. 20 SM, 1 ea. 40 SM.

CLEAR LAYFLAT POLYETHYLENE TUBING/DUCTING

Suitable for positive ventilation air and drying. Not for suction use. Not electrically conductive. 4 mil thickness.

Sizes: 10" to 26" ID **Length:** Roll is approximately 500'.



VENTILATION / BLOWER DUCT

Compact, light weight, single ply, designed for maximum air handling capabilities. Dual direction flow with low friction loss. For use with blowers and fans for fume removal or to bring fresh air in enclosed areas.

Sizes: 4" thru 20" **Compression Ratio:** 10:1



VBD-V Constructed of polyester fabric coated with vinyl and reinforced with spring steel helix wire and bonded black wear strip.

Material: Polyester/Vinyl
Temperature Range: -20°F to 180°F

VBD-1200x50 12' x 50' Vinyl coated polyester duct with belted cuffs in a carry bag.

Material: Polyester/Neoprene
Temperature Range: -40°F to 250°F



AIR HOSE COUPLING

Brass coupling has female threaded pin lug connection for use with the ship's male threaded air outlet M42 x 2 (JIS B 0207). The conical shaped insert provides a metal-to-metal mechanical seal.



Part #	Shank Size
7335-15	6mm
7335-35	9mm
7335-45	12mm
7335-55	15mm
7335-65	19mm
7335-75	25mm
7335-HC	Hose Cap

Also available in stainless steel.
Order 7335S-XX.



PIN-LUG HOSE CAP with Chain

1-1/2" NST Stainless steel.
P/N: 662-P-150-SS.



Line Type: PN 200L-L-20/30A



Plug x Male
40PM



Plug x Female
40PF



Plug x Hose Barb
40PH

Plugs & couplers available in stainless steel or chrome



4380 S. Wayside, Suite 100, Houston, TX 77087
Phone: 713-641-2288 • 800-532-2672 • Fax: 713-641-3636
sales@accordintl.com, ventas@accordintl.com • www.accordintl.com



Coupler x Male
40SM



Coupler x Female
40SF



Coupler x Hose Barb
40SH