

ACCORD INTERNATIONAL, INC.

## MECHANICAL COIL PACKINGS

*When ordering, specify size and length.*

### PTFE/SYNTHETIC FIBER PACKING



**Accord Style No. 2500**

**Description:** Fibers are individually impregnated with PTFE and then braided, after which the final packing is impregnated (under pressure) with PTFE.

**Applications:** Used for pumps. Service to 260°C (500°F); pH 0-14; operating speeds to 2000 FPM.

**Sizes:** 1/8" to 1"

### ARAMID FIBER COMPRESSION PACKING

**Accord Style No. 3100**

**Description:** Aramid fiber yarn impregnated with TFE and treated with an additional high temperature lubricant. Diagonal weave. Permits operating speeds to 1900 FPM. Service to 260°C (500°F); pH 4-11.

**Applications:** Multi-service for pumps and valves.

**Sizes:** 1/8" to 1"



### TFE BLEACHED, PRESHRUNK, MULTI-FILAMENT BRAIDED YARN PACKING



**Accord Style No. 2290**

**Description:** TFE Fluorocarbon fiber. Can withstand compression forces up to 60,000 psi. Packing is impregnated with TFE resin dispersion (35% by weight). Temperature range: -120°F (-85°C) to 500°F (260°C). Interlock/interbraid construction.

**Applications:** Use packing for valves against chemicals, solvents, and acids, liquid or gas. Non-toxic.

**Sizes:** 1/8" to 2"

### HEAT-RESISTANT TFE MULTI-FILAMENT BRAIDED YARN PACKING



**Accord Style No. 2280**

**Description:** Contains 30% TFE dispersion on yarns and a clear, colorless, non-toxic, heat-resistant lubricant which is applied to yarns before braiding. Interlock construction.

**Applications:** Use packing for rotary pumps against chemicals, solvents, and acids—liquid or gas.

**Sizes:** 1/8" to 2"

### MULTI-SERVICE CARBON YARN PACKING

**Accord Style No. 651**

**Description:** Interbraided carbon yarn, coated with a three-component lubricant system of graphite flake, high temperature lubricant and a sacrificial break-in lubricant. For water, steam, brine, condensate, oils, and fuel to 315°C and shaft speeds to 18 m/sec, pH 0-14.

**Applications:** Boiler feed, lubricating oil, condenser, and condenser extractor, fuel oil and transfer pumps.

**Sizes:** 1/8" to 1"

### SQUARE-BRAIDED GLASS FIBER TFE PACKING

**Accord Style No. 3000**

**Description:** Square braided from long-filament glass yarn. Packing is sealed and lubricated with TFE suspenoid.

**Applications:** Pumps, compressors, mixers, valves and acid handling equipment. Service to 500°F (260°C); pH 4-10.

**Sizes:** 1/8" to 1"

**"Se Habla Español"**

4380 South Wayside  
Suite 100  
Houston, TX 77087

**ACCORD**  
INTERNATIONAL, INC.

Phone: 713-641-2288  
Fax: 713-641-3636  
Toll Free: 800-532-2672  
sales@accordintl.com  
ventas@accordintl.com  
www.accordintl.com