


268



359




243-BT




472-BT

336-S



336-L

363-M



874-BR Brass Universal Spanner Wrench



872-SW Aluminum Tabor Spanner Wrench

843-BT Tank Cleaning Coupling Wrench
for 2-1/2" NST Couplings

ACCORD INTERNATIONAL, INC.

7233 S-W Cast Iron Spanner Wrench
for Storz Fire Hose Couplings358-2525-57
Double Male 2-1/2" NST Adapter
for Joining Two Tank Cleaning
Hose Couplings. Brass.**268-BR Short Shank Couplings**

Are cast of high grade red brass for maximum strength. Recommended when hose is used around salt water, in mines and when non-sparking coupling is needed. Pin lug feature.

P / N. Brass	Size & Threads
268-BR-150 NST	1-1/2" x 1-1/2" NST
268-BR-250 NST	2-1/2" x 2-1/2" NST

359 Double Female Hex Coupling

P / N.	Size & Threads
359-15	1-1/2" F NPT x 1-1/2" NST
359-25	2-1/2" F NPT x 2-1/2" NST

243-BT Tank Cleaning Coupling

Couplings are made of cast brass and furnished complete with four bolt clamps. Please specify thread type when ordering.

P / N. Brass	P / N. Stainless Steel	Shank Size	Thread
243-BSP-150C	243-BSP-150C-SS	1-1/2"	1-1/2" BSP
243-BT-1525 NSL	243-BT-1525 NSL-SS	1-1/2"	2-1/2" NST
243-BT-225 NSL	243-BT-225 NSL-SS	2"	2-1/2" NST

472-BT Tank Cleaning Wye

This wye is made of cast brass and is used for connecting three lengths of hose.

P / N.	Size & Threads
472-BT	2-1/2" M NST x 2-1/2" M NST x 2-1/2" M NST

363-M Male Swivel Adapters

Available with pin lug or rocker lug swivel

P / N.	Size & Threads
363-M-02	1-1/2" F NST x 1-1/2" M NPT
363-M-05	2-1/2" F NST x 2" M NPT
363-M-07	2-1/2" F NST x 2-1/2" M NPT
363-M-08	2-1/2" F NST x 3" M NPT

336-S International Ship Connection

Ship connection is for use with 336-L Shore connection. Flange is threaded with a 2-1/2" female hose thread and **slotted** so that it can be used with non-standard flanges. Connection is supplied complete with bolts, nuts, washers and gaskets.

336-L International Shore Connection

Shore connection is a 2-1/2" x 7" O.D. Flange threaded with 2-1/2" hose thread to match hose threads on docks. Flange is **drilled** to ASA Standards and is supplied complete with bolts, nuts, washers and gaskets.



170U



171U



25-NRSGV

Angle Valves

Cast brass.
Available in 1-1/2" and 2-1/2" sizes.
Please specify UL label when ordering.
170U F (NPT) x M (specify NST or NPSH)
171U F (NPT) x F (NPT)

25-NRSGV Fire Hose Valve

300# Non-rising stem gate valve. Brass construction. Please specify UL label when ordering.
2-1/2" F NPT x 2-1/2" M NST threads.



Marpol Flanges are often referred to as International Slop Flanges. These flanges are available blind or bored out to match nominal pipe sizes from 2" to 5" ID. The flange has 6 slots, 7" PCD (Pitch Circle Diameter), and 8-1/2" OD. Marpol flanges are typically used for oil discharge. Accord will manufacture according to your specifications provided (i.e., male or female pipe thread NPT, fire hose thread NSTNH, Storz, Nakajima, etc.).

"Se Habla Español"

ACCORD
INTERNATIONAL, INC.

4380 S. Wayside, Suite 100, Houston, TX 77087
Phone: 713-641-2288 • 800-532-2672 • Fax: 713-641-3636
sales@accordintl.com, ventas@accordintl.com • www.accordintl.com