

FIRE HOSES

No. 92 - Single Jacket 400 PSI Fire Hose UL Labeled

Service Pressure: 200 PSI
Test Pressure: 400 PSI

No. 92 - Single Jacket 500 PSI Fire Hose UL Labeled

Service Pressure: 250 PSI
Test Pressure: 500 PSI

No. 92 - Double Jacket 600 PSI Fire Hose UL Labeled

Service Pressure: 300 PSI
Test Pressure: 600 PSI

No. 92 - Double Jacket 800 PSI Fire Hose UL Labeled

Service Pressure: 400 PSI
Test Pressure: 800 PSI

No. 95 - Single Jacket 250 PSI Mill Hose

Service Pressure: 125 PSI
Test Pressure: 250 PSI

- Black EPDM tube
- White polyester staple cover
- Fitted with Storz, Nakajima, John Morris (British Instantaneous), Machino, etc.
- Available in 150 PSI Service Pressure and 300 PSI Test Pressure

No. RC500SJ - Single Jacket Rubber Fire Hose - 500 PSI

Service Pressure: 250 PSI
Test Pressure: 500 PSI

- Deep ribbed pattern resists abrasion.
- Red nitrile synthetic rubber one-piece cover and tube/liner.
- Resists most chemicals.
- Meets UL and Factory Mutual Standards.
- 1-1/2" & 2-1/2" fitted with NST Rocker Lug couplings. Also available uncoupled, or fitted with Storz, Nakajima, John Morris (British Instantaneous), Machino.



Coupled with NST

- Heavy duty rubber lined
- Black EPDM tube
- White polyester cover
- Fitted with brass NST Rocker Lug couplings

Part Number*	I.D. Size	Available Lengths
SJ4-92-15xx	1-1/2"	50', 75', 100'
SJ4-92- 25xx	2-1/2"	50', 75', 100'
SJ5-92-15xx	1-1/2"	50', 75', 100'
SJ5-92- 25xx	2-1/2"	50', 75', 100'

Part Number*	I.D. Size	Available Lengths
DJ6-92-15xx	1-1/2"	50', 75', 100'
DJ6-92- 25xx	2-1/2"	50', 75', 100'
DJ8-92-15xx	1-1/2"	50', 75', 100'
DJ8-92- 25xx	2-1/2"	50', 75', 100'

Part Number*	I.D. Size	Available Lengths
SJ25-95-15xx	1-1/2"	50', 66', 75', 100'
SJ25-95- 20xx	2"	50', 66', 75', 100'
SJ25-95- 25xx	2-1/2"	50', 66', 75', 100'

Part Number*	I.D. Size	Available Lengths
RC500SJ-15xx	1-1/2"	50', 66', 75', 100'
RC500SJ-20xx	2"	50', 66', 75', 100'
RC500SJ- 25xx	2-1/2"	50', 66', 75', 100'

* Insert length of hose desired in place of xx.

Available with
UL label or
Wheel Mark.



Part Number*	I.D. Size	Available Lengths
Booster-15xx	1-1/2"	Up to 400' continuous

1-1/2" I.D. Heavy Duty Red Cover Booster Hose

- 250 PSI WP, USCG approved, maximum continuous length is 400', custom assembled lengths-to-order. Tube: NBR/PVC, RMA Class A, Cover: EPDM, Reinforcement: 4-Spiral aramid yarn, Temp. Range: -40°F (-40°C) to +190°F (+88°C), Weight: 0.71 lb/ft (1.06 kg/m), Fittings: Brass NST, NPSH rocker lug couplings, Nakajima, Storz, or British Instantaneous.



"Se Habla Español"

4380 South Wayside
Suite 100
Houston, TX 77087

ACCORD
INTERNATIONAL, INC.

Phone: 713-641-2288
Fax: 713-641-3636
Toll Free: 800-532-2672
sales@accordintl.com
ventas@accordintl.com
www.accordintl.com