

SEA-LINK PRODUCTS

**MANILA ROPE  
STEEL SHELL  
BLOCKS**



SL250 Single Sheave with Fixed Hook



SL250 Double Sheave with Shackle



SL320 Double Sheave with Swivel Hook



SL320 Double Sheave with Fixed Hook

	Block Size in.	Rope Diam.	Sheave Size, Inches			Approx. Weight Lbs.	Working Load Limit Lbs.	Model Numbers*			
			Out-side Diam.	Rim Thick-ness	Center Pin Diam.			With Fixed Hook	With Swivel Hook	With Oblong Swivel Eye	With Drilled Swivel Eye & Shackle
<b>SL250 Series Steel Shell Blocks</b>											
<b>SINGLE SHEAVE BLOCK</b>	3	3/8	1-3/4	1/2	3/8	1	500	SL251B-3H	SL251B-3SH	SL251B-30S	SL251B-3DS
	4	1/2	2-1/4	5/8	3/8	1-3/8	1000	SL251B-4H	SL251B-4SH	SL251B-40S	SL251B-4DS
	5	5/8	3	3/4	3/8	2-1/4	1200	SL251B-5H	SL251B-5SH	SL251B-50S	SL251B-5DS
	6	3/4	3-1/2	1	1/2	4	1800	SL251B-6H	SL251B-6SH	SL251B-60S	SL251B-6DS
	8	7/8 - 1	4-3/4	1-1/8	5/8	7	2800	SL251B-8H	SL251B-8SH	SL251B-80S	SL251B-8DS
	10	1-1/8	6-1/4	1-1/4	5/8	13-1/2	4000	SL251B-10H	SL251B-10SH	SL251B-100S	SL251B-10DS
<b>DOUBLE SHEAVE BLOCK</b>	3	3/8	1-3/4	1/2	3/8	1-3/8	800	SL252B-3H	SL252B-3SH	SL252B-30S	SL252B-3DS
	4	1/2	2-1/4	5/8	3/8	2-1/2	1400	SL252B-4H	SL252B-4SH	SL252B-40S	SL252B-4DS
	5	5/8	3	3/4	3/8	4	1800	SL252B-5H	SL252B-5SH	SL252B-50S	SL252B-5DS
	6	3/4	3-1/2	1	1/2	6	2500	SL252B-6H	SL252B-6SH	SL252B-60S	SL252B-6DS
	8	7/8 - 1	4-3/4	1-1/8	5/8	11	3800	SL252B-8H	SL252B-8SH	SL252B-80S	SL252B-8DS
	10	1-1/8	6-1/4	1-1/4	5/8	21	6000	SL252B-10H	SL252B-10SH	SL252B-100S	SL252B-10DS
<b>TRIPLE SHEAVE BLOCK</b>	3	3/8	1-3/4	1/2	3/8	2	1200	SL253B-3H	SL253B-3SH	SL253B-30S	SL253B-3DS
	4	1/2	2-1/4	5/8	3/8	3-1/2	1800	SL253B-4H	SL253B-4SH	SL253B-40S	SL253B-4DS
	5	5/8	3	3/4	3/8	5	2400	SL253B-5H	SL253B-5SH	SL253B-50S	SL253B-5DS
	6	3/4	3-1/2	1	1/2	9-1/2	3200	SL253B-6H	SL253B-6SH	SL253B-60S	SL253B-6DS
	8	7/8 - 1	4-3/4	1-1/8	5/8	15	4800	SL253B-8H	SL253B-8SH	SL253B-80S	SL253B-8DS
	10	1-1/8	6-1/4	1-1/4	5/8	26	8000	SL253B-10H	SL253B-10SH	SL253B-100S	SL253B-10DS
<b>SL320 Series Malleable Iron Style Steel Shell Blocks</b>	3	3/8	1-3/4	1/2	3/8	1-1/2	700	SL321B-3H	SL321B-3SH	SL321B-30S	SL321B-3DS
	4	3/8 - 1/2	2-1/4	5/8	3/8	2-1/4	1100	SL321B-4H	SL321B-4SH	SL321B-40S	SL321B-4DS
	6	5/8 - 3/4	3-1/2	1	1/2	5-1/2	2000	SL321B-6H	SL321B-6SH	SL321B-60S	SL321B-6DS
	8	7/8 - 1	4-3/4	1-1/8	5/8	10	3300	SL321B-8H	SL321B-8SH	SL321B-80S	SL321B-8DS
	10	1-1/4	6-1/4	1-1/2	3/4	19-1/2	5000	SL321B-10H	SL321B-10SH	SL321B-100S	SL321B-10DS
	12	1-1/2	8	1-5/8	3/4	30	8900	SL321B-12H	SL321B-12SH	SL321B-120S	SL321B-12DS
<b>DOUBLE SHEAVE BLOCK</b>	3	3/8	1-3/4	1/2	3/8	2	1000	SL322B-3H	SL322B-3SH	SL322B-30S	SL322B-3DS
	4	3/8 - 1/2	2-1/4	5/8	3/8	3-3/4	1600	SL322B-4H	SL322B-4SH	SL322B-40S	SL322B-4DS
	6	5/8 - 3/4	3-1/2	1	1/2	9-1/4	3300	SL322B-6H	SL322B-6SH	SL322B-60S	SL322B-6DS
	8	7/8 - 1	4-3/4	1-1/8	5/8	16-1/2	5100	SL322B-8H	SL322B-8SH	SL322B-80S	SL322B-8DS
	10	1-1/4	6-1/4	1-1/2	3/4	30-1/2	7700	SL322B-10H	SL322B-10SH	SL322B-100S	SL322B-10DS
	12	1-1/2	8	1-5/8	3/4	46	15600	SL322B-12H	SL322B-12SH	SL322B-120S	SL322B-12DS
<b>TRIPLE SHEAVE BLOCK</b>	3	3/8	1-3/4	1/2	3/8	2-1/2	1400	SL323B-3H	SL323B-3SH	SL323B-30S	SL323B-3DS
	4	3/8 - 1/2	2-1/4	5/8	3/8	5	2200	SL323B-4H	SL323B-4SH	SL323B-40S	SL323B-4DS
	6	5/8 - 3/4	3-1/2	1	1/2	12-1/2	4000	SL323B-6H	SL323B-6SH	SL323B-60S	SL323B-6DS
	8	7/8 - 1	4-3/4	1-1/8	5/8	22	7000	SL323B-8H	SL323B-8SH	SL323B-80S	SL323B-8DS
	10	1-1/4	6-1/4	1-1/2	3/4	40	10000	SL323B-10H	SL323B-10SH	SL323B-100S	SL323B-10DS
	12	1-1/2	8	1-5/8	3/4	70	17900	SL323B-12H	SL323B-12SH	SL323B-120S	SL323B-12DS

\* For Upset Shackle or Regular Shackle top fitting, change suffix to US or RS, respectively.

DO NOT EXCEED WORKING LOAD LIMITS

FACTORY CERTIFICATE OF CONFORMANCE INCLUDED WITH EACH BLOCK

**Associated Wire Rope & Rigging, Inc.**  
8125 Saran Avenue  
Playa del Rey, CA 90293  
Tel: 310-448-5444 or 800-901-1135  
Fax: 310-448-5446  
sales@awrrinc.com



AVAILABLE TO MEET  
U.S. FEDERAL SPECIFICATIONS

**Waterman Supply Co., Inc.**  
P.O. Box 596  
Wilmington, CA 90748-3131  
Tel: 310-522-9698 or 800-322-3131  
Fax: 310-522-1043  
sales@watermansupply.com