

DENSO NORTH AMERICA

PETROLATUM TAPE


Denso Petrolatum Tape is composed of a non-woven synthetic fabric carrier, fully impregnated with a petrolatum compound. The tapes provide long-term corrosion protection to pipes, flanges, valves and hydraulic lines & fittings.

Features:

- Applied to marginally prepared surfaces (SSPC SP 2/3)
- Can be applied to cold, wet surfaces
- Contains no solvents
- Easy application from arctic to tropical temperatures
- Contours to irregular shapes & profiles

**Property Specifications:**

Thickness (ASTM D1000)	46 mils
Weight	.295 lbs/ft ²
Breaking Strength (ASTM D1000)	22.5 lbf/in.
Elongation @ Break	10%
Resistance to Acids, Alkalis & Salt	Excellent
Primer	Denso Paste

**Quantity Estimates**

Tape Width	Rolls*/Case	Coverage with 1" Overlap	Coverage with 55% Overlap
2"	36	87 ft ² /case	87 ft ² /case
4"	18	145 ft ² /case	87 ft ² /case
6"	12	162 ft ² /case	87 ft ² /case
8"	8	150 ft ² /case	77 ft ² /case
12"	6	177 ft ² /case	87 ft ² /case

* All rolls are 33 feet in length

PROTECTIVE FIBERGLASS OUTERWRAP

Denso Glass Outerwrap is a fiberglass cloth impregnated with a water-activated resin that is used as a protective outer wrap over Petrolatum Tape. It offers exceptional mechanical and impact strength for underwater, underground and above ground pipe and piles.

**Features:**

- Resists cold and hot temperatures
- Easy to apply – no mixing or messy clean up
- Resistant to water, acid, salts or soil organics
- Can be applied underwater or to wet surfaces
- Minimal surface preparation required
- Quick, long term protective coating, ready for immediate service
- Contains no solvents
- Can be top coated for aesthetics

Tape Width	Roll Length	Rolls†/Case	Coverage with 50% Overlap
3"	9'	15	17 ft ² /case
4"	30'	5	25 ft ² /case
8"	40'	3	40 ft ² /case

† If other widths or lengths are required, specify when ordering.

UNDERWATER EPOXY MASTIC



SeaShield SplashZone UW Epoxy is a solvent-free patching compound used for repairing pits, cracks and voids in steel, concrete, wood and other surfaces. It can be mixed, applied and cured underwater.

2 gallon kit –
1 gallon of part A base
1 gallon of part B hardener

Features:

- 100% solids
- Resists wave action
- Designed for underwater and other wet applications
- Can be applied up to 2" in thickness
- Self-priming on most surfaces and over most generic coatings
- Underwater rapid cure characteristics
- VOC free

1-281-821-3355
www.densona.com

9747 Whithorn Drive • Houston, TX 77095
Fax: 281-821-0304 • info@densona.com

Denso[®]
DENSO NORTH AMERICA

First Petrolatum Tape manufactured in the UK was Denso Tape. Denso provides petrolatum tape for anti-corrosion protection on ships and vessels.

Products include:
Denstyl Tape • Denso LT Tape • Denso Paste