

PHOENIX LIGHTING

MARINE RATED SNAPLIGHT – LFSB Series



LFSB-2-17-UNIV – 2 Lamp, F17 T-8 (medium bi-pin, 2 foot), 120-277V; 50/60Hz

LFSB-2-32-UNIV – 2 Lamps, F32 T-8 (medium bi-pin, 4 foot), 120-277V; 50/60Hz

Linear fluorescent fixture rated for wet locations and ABS certified. Marine grade components for superior corrosion resistance. Vibration-resistant, spring-loaded lamp holders for demanding applications. Available in two and four foot lengths.

Construction	Corrosion-resistant, impact-resistant, UV-stabilized nylon housing Thermoset high reflectance, white polyester powder coated reflector
Hardware	Stainless steel external hardware
Lamp holders	Vibration-resistant, spring-loaded lamp holders
Lens	High-impact polycarbonate matte finish diffuser
Light Source	17W or 32W fluorescent lamps Lamps not included
Power source	120-277V, 50/60Hz (UNIV) Low temperature ballast - standard
Wiring	¾ inch NPT threaded conduit openings on both ends Threaded plug and cable gland provided Through wiring - standard (max two lamp 32W) Terminal block - standard
EMB	120/277V, 60Hz
Mounting	Stainless steel mounting feet
Weight	2 foot (packaged) - 8.7 lb (3.9 kg) 4 foot (packaged) - 13.4 lb (6.1 kg)
Warranty	1 year

Compliances:

UL/cUL Listed to:

- UL 1598 Suitable for Wet Locations
- UL 1598A Marine Inside Type Dripproof
- UL 1598A Marine Outside Type (Saltwater)
- UL 924 Emergency Lighting Equipment

ABS

IP65 rated

Dimensions:**2-Foot**

Width: 7.70" (196mm)
Height: 4.90" (125mm)
Length: 28.90" (734mm)

4-Foot

Width: 7.56" (192mm)
Height: 4.90" (125mm)
Length: 53.00" (1346mm)

Options and Accessories:

EMB – Emergency Battery Backup