

## PHOENIX LIGHTING

## SUPER-ROUGH SERVICE FLOODLIGHT – MRS Series

**MRS 64/1000** – Halogen - PAR64, 1000W Fixture

Super-rough service floodlight rated for wet locations. Designed to withstand the most extreme shock and vibration. For use in above-deck marine applications and other demanding environments.

Construction	Copper-free, cast aluminum housing and door
Finish	Phoenix green thermoset powder coat
Hardware	Stainless steel external hardware
Lens	Heat-resistant, heavy duty tempered clear cover lens - standard Red and yellow accessories available
Aiming	Dual axis with full grip locking levers
Light Source	Halogen - PAR64, 1000W Extended mogul end prong lamps Lamp not included
Power source	120V, 60Hz
Wiring	4 foot (1.2 m), 3-conductor SEO cord
Mounting	Copper-free, cast aluminum mounting bracket Shock mount base option available (SMB)
Weight	22.0 lb (10.0 kg)
Warranty	1 year

**Compliances:**

UL/cUL Listed to:

- UL 1598A Marine Outside Type (Saltwater)
- UL 1598 Suitable for Wet Locations

CSA Certified Indoor/Outdoor Type 4X  
ABS

**Dimensions:**

Width: 14.00" (356mm)

Height: 17.30" (439mm)

Depth: 10.70" (272mm)

Base Width: 3.80" (97mm)

**Options and Accessories:**

WG-4	Wire Lens Guard
GL-R	Red Glass Cover Lens
GL-Y	Yellow Glass Cover Lens
SMB	Shock Mount Base