

DBI-SALA FALL PROTECTION

Full Body Harnesses

These harnesses are light-weight for added mobility and feature the Delta no-tangle design and "stand-up" back D-ring. Straps are color-coded for easy donning, and the 5 point adjustment system provides accurate adjustability and a custom fit. Universal size fits most. Meets ANSI and OSHA Standards.



Part No.	Description
1102000	Vest Style, Back D-ring, Tongue Buckle Legs
1102008	Vest Style, Back & Side D-rings, Tongue Buckle Legs
1107800	Vest Style, Back & Front D-rings, Tongue Buckle Legs
1102950	Cross-Over, Back & Front D-rings, Tongue Buckle Legs

Full Body Derrick Harnesses

1108125

Designed for the oil industry and for the specialty functions on the derrick. All feature the Delta no-tangle design, color-coded straps for easy donning, and a 5 point adjustment system providing accurate adjustability and a custom fit. Meets ANSI and OSHA Standards.



1105825

Part No.	Description
1108125	Bosun Chair Harness, Hi-Vis Web & Built-in Seat Board
1105825	Derrick Harness (shown with 1000544 belt)

Descent Devices for Vertical and Sloped Applications

These Descent Devices will get personnel down safely from high places when quick escape is vital. Either vertical or sloped models are available to provide complete versatility and flexibility for any job site or work environment. No power source or special skills or tools are required. Low speed and high speed models available with stainless steel or galvanized cable lifelines.

Part No.	Length	Retraction	Type
3303000	115' Galv.	Automatic	Vertical
3303001	115' S.S.	Automatic	Sloped
3303018	200' S.S.	Manual	Vertical
3303016	200' S.S.	Manual	Sloped

Sealed Self Retracting Lifelines

Sealed SRL has a corrosion-resistant cast aluminum/stainless steel housing. It separates all dynamic components, including the motor spring and self-adjusting disc brake, from foreign elements such as grease, moisture and dirt. The 3/16" stainless steel cable features a self-locking swivel snap hook with impact indicator. Meets ANSI and OSHA Standards.



15-130' Models

Part No.	Description
3400827	15' Sealed SRL
3400802	30' Sealed SRL
3400902	50' Sealed SRL
3400862	85' Sealed SRL
3400967	130' Sealed SRL
3400612	175' Non-Sealed SRL

Shock Absorbing Lanyards

These stretchable shock absorbing lanyards offer freedom of movement while reducing trip hazards, dragging and snagging. When not pulled taut, the 6' long lanyard contracts to 4-1/2 feet.

Device limits fall arrest forces to 900 lbs. or less.

A twin-leg model is also available for 100% tie-off. Meets ANSI and OSHA Standards.



Part No.	Description
1244306	6' Shock Absorbing Lanyard
1244406	6' Twin-Leg Shock Absorbing Lanyard, Snap Hooks
1244409	6' Twin-Leg Shock Absorbing Lanyard, Alum. Rebar Hooks
1244412	6' Twin-Leg Shock Absorbing Lanyard, Steel Rebar Hooks

Anchorage Connectors

These carabiner gate openings automatically close and lock, ensuring a secure hold. The Tie-Off Adapter features pass-through type D-rings on either end of a 1-3/4" web wide polyester strap. Our cable choker is 7x19 3/8" stainless steel with pass thru O-rings. Meets ANSI and OSHA Standards.

Part No.	Description
2000112	3/4" Carabiner
2000113	1-3/16" Carabiner
2000114	2" Carabiner
1003000	3' Tie-Off Adapter
1003006	6' Tie-Off Adapter
5900551	6' Cable Choker



RELIABLE | SAFETY | PRODUCTS

TradeNet ID 71412

Alexander/Ryan Marine & Safety
 2000 Wayside Drive • Houston, TX 77011 USA
 Tel: +1 713 923 1671 • Toll Free: 1 800 923 1672
 www.alexanderryan.com
 SalesNola@alexanderryan.com