

PERKO, INC.

SPECIAL PURPOSE LIGHTS FOR USE ON VESSELS OF ANY LENGTH



Fig. 1111ME

SPECIAL FLASHING YELLOW BARGE LIGHT

Sheet Metal—Galvanized Steel

- Complete with Medium PreFocus Socket & Watertight Terminal Tube for 16/3-SO Cable
- Sealed Flasher Unit
- Watertight Access Cap for Rebulbing and Cleaning
- 120V Bulb not included

Designed to meet U.S. Federal Inland Requirements for flashing yellow 180 -225 light for barges, canal boats, etc., that are being pushed ahead or towed along side of a tug boat. For use on 120V A.C. only. Federal Requirements for this light are applicable for: inland waters, Atlantic, Pacific and Gulf coasts, intercoastal waterways and western rivers. Refer to the U.S. Inland Navigation Rules for application, configuration and technical details.

GALVANIZED STEEL (pre-primed) — Cat. No. 1111ME1GAL

Overall Height: 12" **Lens Height:** 6-3/4" **Visibility:** 2 miles

Visibility Arc: 225° **Flashes Per Minute:** 50-70 **Weight:** 6-5/8 lbs.

Important Bulb Data

To comply with Federal Requirements this light must use a PERKO Cat. No. **0342004CLR** bulb or **0342RS4CLR** bulb when a "Rough Service" bulb is required.

Spare Parts Ordering Information

Cat. No.	Item
0133	Flasher
1119	Cap O-Ring
0256001YLW	Lens
0347A00	Med. Prefocus Socket
1105000BLK	Cap, Retainer & O-Ring



Fig. 1129BA

PANAMA CANAL BLUE STEERING LIGHT

Black Plastic

Complete with Pre-Wired Contact Socket and 3 feet of 16/3-SJO Cable For 12, 24, 32 or 120V. Watertight access cap for rebulbing and cleaning. Bulb not included.

Cat. No. 1129BA0BLK

Overall Height: 7-1/2" **Lens Height:** 4-1/2"

Visibility Arc: 135° **Weight:** 3-1/8 lbs.

Important Bulb Data

To comply with Panama Canal Requirements, the light above must use a PERKO Fig. No. **0374** bulb.



Spare Parts Ordering Information

Required Bulbs

12V – Cat. No. **0374001CLR**
 24V – Cat. No. **0374002CLR**
 32V – Cat. No. **0374003CLR**
 120V – Cat. No. **0374004CLR**

Cat. No.	Item
0249000BLU	Lens
1119	Cap O-Ring
0134	Double Contact Socket
1105000BLK	Cap, Retainer & O-Ring



ALL-ROUND LIGHTS

For Use On Vessels 20 Meters (65.6 ft.) to 50 Meters (164.0 ft.) in Length



Fig. 0309A

Description	Plain Bronze Cat. No.		Chrome Plated Bronze Cat. No.	
	Pedestal Base	Pipe Mount Base	Pedestal Base	Pipe Mount Base
White All-Round Light	0112A00PLB	0309A00PLB	0112A00CHR	0309A00CHR
Red All-Round Light	0112RA0PLB	0309RA0PLB	0112RA0CHR	0309RA0CHR
Green All-Round Light	0112GA0PLB	0309GA0PLB	0112GA0CHR	0309GA0CHR
Yellow All-Round Light	0112MA0PLB	0309MA0PLB	0112MA0CHR	0309MA0CHR

Important Bulb Data

To comply with U.L. Standard 1104, the lights listed on this page must use one of the following bulbs:

Required Bulbs

12V – Cat. No. **0374001CLR**
 24V – Cat. No. **0374002CLR**
 32V – Cat. No. **0374003CLR**
 120V – Cat. No. **0374004CLR**



Fig. 0112A

Cast Bronze

Plain or Chrome Plated, Complete with Double Contact Electrical Socket for 12, 24, 32 or 120V. Visibility—2 miles. Bulb included.

Fig. No.	Height Overall Inches	Dia. Base Inches	Tapped Pipe Size Inches	Weight Pounds
0112A	8-3/4	3-1/8	—	2-1/2
0309A	6-1/2	—	1/2	2-1/4

Spare Parts

Fig. 0112A & 0309A

Cat. No.	Item
0106000WHT	White Globe
0106000RED	Red Globe
0106000GRN	Green Globe
0106000YLW	Yellow Globe
0276002	Double Contact Socket



RELIABLE | SAFETY | PRODUCTS

TradeNet ID 71412

Alexander/Ryan Marine & Safety

2000 Wayside Drive • Houston, TX 77011 USA

Tel: +1 713 923 1671 • Toll Free: 1 800 923 1672

www.alexanderryan.com

SalesNola@alexanderryan.com