



OPTIONS

- Dual heating (electric & steam) selectable through the control
- Stainless steel side panels
- Stainless steel back panel
- 3rd inlet valve for soft water
- Pneumatic inlet valves for faster filling
- Pneumatic steam valve
- Integrated plinth to increase loading height and ensure ergonomical operation and fit linen carts (Height 6,3 inches to reach bottom loading door of 27,6 inches)

STANDARD FEATURES & BENEFITS

- Freestanding, high spin washer
- Compact & modern space-saving design
- Large loading and unloading doors with up to 180° opening angle for easy access
- Choice of liquid and powder detergent in 5 compartment frontal dispenser
- Standard equipped for automatic soap dosing
- Drum and tub, as well as front and top panel made of robust and durable high quality stainless steel AISI 304
- Ceramic coated shaft for longer life due to less friction on sealing surfaces
- Highly flexible and freely programmable control with advanced 7" colour display for easy operation and perfect management of your laundry business
- USB connection in the front for quick data transfer and data editing on simple .csv format
- On screen photographic illustrated troubleshooting guide
- Clear status light indication for easy and quick visual management
- Large 3" drain valve for fast evacuation and shorter cycles
- Plexi double glass protection against heat
- Accelerometer for perfect balancing

MODEL	UNIT	TWE 10	TWE 15
Dry load	lb	22	35
Performance	lb/h	35	50
Cycle time	min	40-45	40-45
DRUM			
Drum diameter	inches	25	25
Drum depth	inches	12,6	20,5
Drum volume	cu.ft.	3,5	5,4
Wash speed	rpm	34	34
Extraction speed	rpm	1000	1000
G-Force		351	351
DOOR			
Door opening ø	inches	18	18
HEATING			
Electric	BTU	40,710	40,710
Steam	BTU	66,700	66,700
ELECTRIC			
Electric consumption*	HP/h	1,21	1,81
Motor	HP	2	3
STEAM			
Steam valve connection ø	DN-BSP	15-1/2"	15-1/2"
Steam pressure	psi	29-87	29-87
Steam consumption	lb/cycle	11	16,5
AIR			
Air connection ø	inches	optional / 0,31	optional / 0,31
WATER			
Inlet valve connection ø	DN-BSP	2 x 20-3/4"	2 x 20-3/4"
Water inlet (detergent) ø	DN-BSP	-	-
Water pressure	kPa	29-58	29-58
Water flow	gal/min	31,7	31,7
Water consumption*	cold gal/cycle	varies	varies
	hot gal/cycle	varies	varies
Drain valve connection ø (outer)	inches	3	3
Drain flow	gal/min	60	60
PROGRAMMABLE CONTROL			
18 default programmes (max. 99)		Std	Std
7" colour, high-resolution LCD		Std	Std
DIMENSIONS			
Standard WxDxH	inches	35x36x58	35x42x58
with platform 6 inches	inches	35x36x65	35x42x65
Packing WxDxH	inches	35x37x60	35x43x60
with platform	inches	35x37x67	35x43x67
WEIGHT			
Net	lb	914	947
Gross	lb	936	970
Net with platform	lb	981	1025
Gross with platform	lb	1003	1047
SOUND LEVEL			
	db(A)	62-72	62-72

* Consumption figures based on 'Eco 60°C' program (main wash, 2 rinses)