



Washer Extractors TWE 60 - 110

## OPTIONS

- Dual heating (electric & steam) selectable through the control (not on TWE 110)
- Forward tilting
- Extra inlet valve for soft water
- Pneumatic inlet valves for faster filling, standard on TWE 110
- Pneumatic steam valve on TWE 60, standard on TWE 110
- Second drain valve for water recovery
- Weighing cells to measure amount of linen and reduce the water, energy and detergent consumption accordingly

## STANDARD FEATURES & BENEFITS

- Freestanding, high spin washer
- Compact & modern space-saving design
- Large loading and unloading doors with up to 180° opening angle for easy access
- Choice of liquid or powder detergent in 3 or 6 compartment frontal dispenser (available end 2017)  
Now soap dispenser on side with 5 compartments.
- Standard equipped for automatic soap dosing
- Drum and tub, as well as the entire cabinet made of robust and durable high quality stainless steel AISI 304
- Ceramic coated shaft for longer life due to less friction on sealing surfaces
- Highly flexible and freely programmable control with advanced 7" colour display for easy operation and perfect management of your laundry business
- USB connection in the front for quick data transfer and data editing on simple .csv format
- On screen photographic illustrated troubleshooting guide
- Clear status light indication for easy and quick visual management
- Large 3" (TWE 60) or 4" (TWE 110) drain valve for fast evacuation and shorter cycles
- Accelerometer for perfect balancing

MODEL	UNIT	TWE 60	TWE 110
Dry load	lb	132	243
Performance	lb/h	198	364
Cycle time	min	40-45	40-45
<b>DRUM</b>			
Drum diameter	inches	43,3	51,2
Drum depth	inches	24	32,7
Drum volume	gal	20,4	38,9
Wash speed	rpm	34	29
Extraction speed	rpm	770	720
G-Force		360	360
<b>DOOR</b>			
Door opening ø	inches	22	27
<b>HEATING</b>			
Electric	BTU	142,488	n/a
Steam	BTU	66,700	66,700
<b>ELECTRIC</b>			
Electric consumption*	HP/h	8	n/a
Motor	HP	15	30
<b>STEAM</b>			
Steam valve connection ø	DN-BSP	25-1"	40- 1½"
Steam pressure	psi	29-87	29-87
Steam consumption	lb/cycle	62	110
<b>AIR</b>			
Air connection ø	inches	optional / 0,31	0,39
<b>WATER</b>			
Inlet valve connection ø	DN-BSP	2 x 25-1"	2 x 50-2"
Water inlet (detergent) ø	DN-BSP	1 x 25-1"	1 x 25-1"
Water pressure	psi	29-58	29-58
Water flow	gal/min	40	130
Water consumption*	cold gal/cycle	110	200
	hot gal/cycle	30	60
Drain valve connection ø (outer)	inches	3	3
Drain flow	gal/min	60	60
<b>PROGRAMMABLE CONTROL</b>			
18 default programmes (max. 99)		Std	Std
7" colour, high-resolution LCD		Std	Std
<b>DIMENSIONS</b>			
Standard WxDxH	inches	65x62x76	73x77x82
Tilting WxDxH	inches	71x63x85	78x79x89
Packing WxDxH	inches	67x65x82	77x89x88
Packing Tilting WxDxH	inches	75x69x90	83x91x95
<b>WEIGHT</b>			
Net	lb	4079	9193
Gross	lb	4134	9303
<b>SOUND LEVEL</b>			
	db(A)	67-77	70-77

\* Consumption figures based on ,Eco 60°C' program (main wash, 2 rinses)