



LAMPS

Low voltage halogen lamps

	Cat.No.	Volt	Watt	Diam.	Length	Base		Fig.
1	108596	12	5	9	31	BA9s		1
	108603	28	5	11	31	BA9s		1
	108620	12	20	38	41	B15d	32° GBF	2
	108622	12	50	15	35	B15s		3
2	108624	12	50	15	43	B15s	for 110/220V rotating beacon	3
	108694	24	50	15	43	B15s	for 24V rotating beacon	3
	108602	12	10	9	31	G4		4
	108604	12	20	9	31	G4		4
	108606	12	35	9	31	G4		4
	108610	24	20	9	31	G4		4
3	108712	12	50	11	44	G6.35		4
	108722	24	100	11	44	G6.35		4
	108724	24	150	11	44	G6.35		4
	108680	24	60	18	42	GX6.35	SPS-10A for 'Aldis'	5
6	108625	12	20	11	44	GY6.35		4
	108627	12	35	11	44	GY6.35		4
	108634	12	75	11	44	GY6.35		4
	108636	12	100	11	44	GY6.35		4
	108676	24	35	11	44	GY6.35		4
	108678	24	50	11	44	GY6.35		4
7	108681	24	150	11	44	GY6.35		4
	108682	24	250	11	44	GY6.35	for Wolf Turbo-lite	4
	108660	12	55	9	67	P14.5s	H1	6
	108684	24	70	9	67	P14.5s	H1	6
8	108670	6	55	11	42	PK22s	H3	7
	108672	12	55	11	42	PK22s	H3	7
	108690	24	70	11	42	PK22s	H3	7
	108644	12	55	36	49	P36	Thorn 450 for air turbo lamp	8
	108626	12	20	35.3	41	GU4		9
9	108613	12	20	50	46	GU5.3	36° BAB	9
	108615	12	35	50	46	GU5.3	8° FRB	9
	108617	12	45	50	46	GU5.3	36° EXN	9
	108621	28	20	50	46	GU5.3	38° BAB	9
10	108736	24	250	50	45	GX6.35	EMM A1/258	10



4

5

7