



FLUORESCENT LIGHTING OUTDOOR

Watertight lighting fittings (IP65), base: reinforced polyester, shade clear methacrylic
110 Volt DC



Cat.No.	Watt	Length	Width	Height
126180	1X18	667	100	110
126186	2X18	667	170	110

Watertight lighting fittings (IP65), base: reinforced polyester, shade clear methacrylic
110 Volt 60Hz



Cat.No.	Watt	Length	Width	Height
126200	1x18	667	100	110
126206	2x18	667	170	110
126212	1x36	1276	100	110
126218	2x36	1276	170	110

Watertight lighting fittings (IP65), base: reinforced polyester, shade clear methacrylic
220 Volt DC



Cat.No.	Watt	Length	Width	Height
126260	1x18	667	100	110
126266	2x18	667	170	110
126272	1x36	1276	100	110
126278	2x36	1276	170	110

Watertight lighting fittings (IP65), base: reinforced polyester, shade clear methacrylic
220 Volt 50Hz



Cat.No.	Watt	Length	Width	Height
126290	1x18	667	100	110
126296	2x18	667	170	110
126302	1x36	1276	100	110
126308	2x36	1276	170	110

Watertight lighting fittings (IP65), base: reinforced polyester, shade clear methacrylic
220 Volt 60Hz



Cat.No.	Watt	Length	Width	Height
126350	1x18	667	100	110
126356	2x18	667	170	110
126362	1x36	1276	100	110
126368	2x36	1276	170	110