



FLUORESCENT LIGHTING OUTDOOR

Watertight lighting fittings IP67 220V 50/60Hz, stainless steel with electronic HF ballast
make Glamox MIR-S67



Cat.No.	Watt	Length	Width	Height
126394	2x18	838	165	123
126680	2x36	1334	165	128

Shades for fluorescent fittings



1



2



3

Cat.No.	L	W	H	For fitting	Fig	*
126506	658	95	52	126150, 126180, 126200, 126260, 126290, 126350	1	*
126530	658	165	52	126156, 126186, 126206, 126266, 126296, 126356	1	*
126544	690	165	90	Philips TN25, TCT011 2 x 20W opal	2	
126568	688	170	70	Aqua Signal shade type 9840005300 2 x 18W clear	3	
126580	675	142	68	Glamox MIR 2 x 18W clear also for MIX, MIL and MAX	3	
126610	1265	95	52	126162, 126212, 126272, 126302, 126362	1	*
126622	1265	165	52	126168, 126218, 126278, 126308, 126368	1	*
126648	1335	130	70	Aqua Signal shade type 9840005600 2 x 36W clear	3	
126666	1291	140	70	Glamox MIR 2 x 36W clear also for MIX, MIL and MAX	3	

* clear, impact resistant