




CABLES

Silicon cable, flexible with galvanised steel wire outside cover

Test voltage 2000V, -50° C / +180° C



Cat.No.	mm2	Overall diameter
261304	3 x 1.5	9.8

Marine switchboard wire with PVC outside cover

Type VUV, rated voltage 600/1000V. Test voltage 2500, class CS85 (85°).

Approved by the major shipping classification bureaus



Cat.No.	mm2	Overall diameter
260018	1.5	3.8
260020	2.5	4.7
260023	4	6.0
260024	6	9.0

Marine cable with halogen free outer sheath

Rated voltage 600/1000V, flame retardant, 100° C. Main uses and features:
rigid cables for installation in ships with special performances of non fire
propagation and low emission of smoke and fumes.

Approved by the major shipping classification bureaus



Cat.No.	mm2	Overall diameter
260023	1 x 4	5.9
260025	1 x 6	6.5
261511	1 x 10	8.0
261513	1 x 16	9.5
262518	2 x 1.5	8.5
262519	2 x 2.5	9.5
262525	3 x 1.5	8.5
262527	3 x 2.5	10
262530	3 x 4	11.5
262533	3 x 6	12.5
262540	4 x 1.5	10
262541	4 x 2.5	11
262544	5 x 1.5	11
262556	7 x 1.5	13