




## RELAYS AND CONTACTORS

### Relays, plug-in OMRON MY4IN(S) 4-pole c/over, 5A



Cat.No.	Description
442080	24VDC
442084	24VAC
442088	110VAC
442092	230VAC
442096	Socket PYF14A-N for MY4



### Relays, plug-in, with 8 pins (2-pole c/over), 10A




Cat.No.	Coil voltage
442100	6VDC
442104	6VAC 50/60Hz
442108	12VDC
442112	12 VAC 50/60Hz
442116	24VDC
442120	24VAC 50/60Hz
442124	110VDC
442128	110VAC 50/60Hz
442132	220VDC
442136	220VAC 50/60Hz

### Relays, plug-in, with 11 pins (3-pole c/over), 10A



Cat.No.	Coil voltage
442200	6VDC
442204	6VAC 50/60Hz
442208	12VDC
442212	12VAC 50/60Hz
442216	24VDC
442220	24VAC 50/60Hz
442224	110 VAC 50/60Hz
442228	220 VDC
442232	220 VAC 50/60Hz

### Relays, plug-in, with 8 pins (2-pole c/over), for series connection with navigation lamps



Cat.No.	For lamp
442260	24V 40W DC
442272	110V 60W AC
442284	220V 65W AC