

EXPLOSION-PROOF EQUIPMENT

Explosion-proof fixtures up to 200W, flameproof enclosed, brass/red brass casing and glass ring with thread, brass wire guard, complete with E27 lampholder.

Temperature class: incandescent lamp 200W: T3, high pressure mercury vapour lamp 125W: T3, 80W: T4, blended light lamp 160W: T3, compact fluorescent lamp 23W: T6, EN 50 014, 50 018, 50 0191977 Zone 1 Atex approved

Cat.No.	Description
762232	Complete fixture max. 200W E27
762215	Brass stop end M24 x 1.5, can be used when only 1 cable entry is used instead of 2 cable entries
762245	Glass with guard for cat.no. 762232



Explosion-proof floodlights

Cat.No.	Description
765226	Floodlight with E40 lampholder for double-envelope tungsten halogen (iodine) lamps, 120-240V 500W Atex Zone 2, IP67



Other types of the Aqua Signal product assortment available on request

Explosion-proof brass switches. Protection category: IP66

Explosion category: Eex de IIC T6 Atex approved

Cat.No.	Description	Fig.
762410	2-pole, 16A, 250VAC, 0-	1
762412	2-pole, 16A, 250VAC, 0=	
762414	2-pole, 16A, 250VAC, -0-	2
762215	Brass stop end M24 x 1.5, can be used when only 1 cable entry is used instead of 2 cable entries	
762210	Interior 2-pole for switch 762410, 12 and 14	3



1



2



3