



EXPLOSION-PROOF EQUIPMENT

Explosion-proof CEE-plugs, protection category: IP66

Explosion category: Eex de IIC T6, max. 240VAC ATEX approved

Cat.No.	Description	Fig.
762440	Brass, 2-pole and earth 16A	1
762450	Interior for cat.no. 762440	2



1



2

Explosion-proof CEE-receptacles, protection category: IP66

Explosion category: Eex de IIC T 6 ATEX approved



Cat.No.	Description
762460	Brass, 2-pole and earth, 16A, max. 240 VAC, -0
762215	Brass stop end M24 x 1.5, can be used when only 1 cable entry is used instead of 2 cable entries
762470	Interior for cat.no. 762460

Explosion-proof brass junction boxes with cable glands M 24 x 1.5

Protection category: IP56, explosion category: EEx e II T 6 ATEX approved



Cat.No.	Description
762480	With gland position =0
762482	With gland position -0-
762484	With gland position -0=
762486	With gland position =0=
762215	Brass stop end M24 x 1.5, can be used when only 1 cable entry is used instead of 2 cable entries

Explosion-proof bells. 105 dB (A) 3 dB, 1 M. 200 mm diam.

Protection category: IP54, explosion category: EEx de II BT 6 ATEX approved



Cat.No.	Volt	Herz
762704	12 AC	50
762706	24 AC	50
762708	42 AC	50
762712	110 AC	50
762714	120 AC	60
762716	220 AC	50
762718	240 AC	60
762720	12 DC	
762722	24 DC	
762728	110 DC	
762730	220 DC	