



## PRESSURE CONTROLS

### RT pressure controls, ship approved

High repeatability. Interchangeable contact system.  
Two cable entries, IP66. Manual or automatic reset.



**RT 121**



**RT 262A / RT 260A**

### Technical data

Media:	air, gas, liquid		
Media temp.:	-50°C to 150°C, RT113 max. 90° C		
Ambient temp.:	in general: -50° C to 70° C		
Contact system:	SPDT		
Contact load:	AC-1 Ohmic	10A	440V
	AC-3 (motor)	4A	400V
	AC-14/15 (coil. transformer)	3A	400V
	DC-13/14	12W	230V
Connection:	G 3/8" A		

Cat.No.	Setting range (bar)	Adjustable/fixed Differential (bar)	Max. operating pressure (bar)	Type
862300	-1 to 0	0.09 to 0.4	7	RT 121
862302	0 to 0.3	0.01 to 0.05	0.4	RT 113
862304	0.1 to 1.1	0.07 to 0.16	7	RT 112
862306	0.2 to 3	0.08 to 0.25	7	RT 110
862308	0.2 to 6	0.25 to 1.2	22	RT 200
862310	1 to 10	0.15 to 1.3	22	RT 116
862312	4 to 17	1.2 to 4	22	RT 5
862320	10 to 30	1 to 4	42	RT 117

### RT differential pressure controls, connection G3/8 A

Cat.No.	Regulation range (bar)	Mechanical Differential (bar)	Operation Range (bar)	Max. operating Pressure (bar)	Type
862330	0.01 to 1.5	0.1	-1 to 9	11	RT 262A
862336	0.5 to 4	0.3	-1 to 18	22	RT 260A