



THERMOSTATS, RESISTANCE THERMOMETERS AND THERMOCOUPLES

Sensor pockets with 1/2" BSP ext. connection for thermostats

Cat.No.	For type	Insert l x d. mm.	Material
882300	RT 3/7/14/26/101/123/270	112 x 11	brass
882310	RT 3/7/14/26/101/123/270	112 x 11	18/8 steel
882320	KPS	110 x 15	brass
882330	KPS	110 x 15	18/8 steel



KPS thermostats

For harsh environments
IP67

Very robust construction
Various approvals

Ambient temperature:

-40°C to 70 ° C

Contact load:

AC-1	10A	AC-3	6A
AC-15	4A		

Cat.No.	Setting range °C			Mech. diff. °C			Max. sensor temp. °C	Cap. Tube length (m)	Type	Fig.
		to			to					
882400	20	to	60	3	to	14	130	-	KPS 77	1
882404	20	to	60	3	to	14	130	2	KPS 77	2
882402	20	to	60	3	to	14	130	2	KPS 77	3
882406	50	to	100	4	to	16	200	-	KPS 79	1
882408	50	to	100	4	to	16	200	2	KPS 79	2
882410	50	to	100	4	to	16	200	2	KPS 79	3
882412	70	to	120	4.5	to	18	220	-	KPS 80	1
882414	70	to	120	4.5	to	18	220	2	KPS 80	2
882416	70	to	120	4.5	to	18	220	2	KPS 80	3



1



2
armoured



3
non armoured